

Wall Lights | 220-240 V | 2xE14 4402














Finishing diffuser

Technical data		
Installation position	Wall lights - Ceiling	
Installation environment	Indoor	
Lamp cap	2 x E14 Max 30W	
Frequency	50-60 Hz	
Optic	Diff. + Diff. + Diff.	
Light emission direction	downward	
Safety class	1	
IP	IP20	
Glow wire test	850°	
Direct mounting on normally flammable surfaces	Yes	
CE	Yes	
ETL	No	
Emergency mode	No	
Directional	Yes	
Tilting	No	
Walk-over	No	
Drive-over	No	
Cable included	No	
Resin potting	No	

Material	Glass			
Colour	white			
Processing	Sandblasting			
Finishing mounting frame				
Finishing mour	iting frame			
Finishing mour Material	Iting frame Iron			

Campana_W



Wall Lights | 220-240 V | 2xE14 **4402**

Single emission wall lights for indoor application. Compatibility: LED lamp, halogen 30 W, compact fluo 8 W; lamp cap 2xE14.

The diffuser is made of glass with a sandblasting treatment; the mounting frame is made of iron, with a chrome finish, processed by means of electroplating. The ingress protection degree is IP20; the total weight is of 1.180 kg.

The device features protection class I and can be wall lights or ceilingmounted.

Illuminotechnical Features		
Luminous flux (source)	1670 lm	
Colour temperature	2800 K	
Colour rendering index	100 Ra	