

# PRODUCT DATASHEET DECOSTAR 51 PRO 35 W 12 V 36° GU5.3

DECOSTAR 51 PRO | Halogen dichroic reflector lamps with 51 mm diameter



#### **AREAS OF APPLICATION**

- General illumination
- Kitchen lighting
- Dining table lighting
- Mirror lighting
- Workplace lighting
- Shops
- Restaurants, hotels and similar prestigious applications

#### **PRODUCT BENEFITS**

- Brilliant accent lighting
- Significantly lower CO<sub>2</sub> emissions compared to standard version
- Constant luminous intensity and constant color location throughout the lifetime
- Approved for use in open luminaires (to IEC 60598-1)
- UV filter
- Contains no mercury

#### **PRODUCT FEATURES**

Average life: 5,000 h100 % dimmable

Color rendering index R<sub>a</sub>: 100
 Color temperature: 3,000 K

Diameter: 51 mmDeco cover

- IRC technology

# **TECHNICAL DATA**

# Electrical data

Nominal wattage	35.00 W	
Nominal voltage	12 V	
Rated wattage	35.00 W	
Power factor λ	1.00	
Claimed equiv. conventional lamp power	50 W	


#### Photometrical data

Nominal useful luminous flux 90°	620 lm		
Luminous intensity	2200 cd		
Rated color temperature	3000 K		
Light color (designation)	Warm White		
Color rendering index Ra	100		
Lumen main.fact.at end of nom.life time	0.75		
Rated useful luminous flux 90°	620 lm		
Rated peak intensity	2200 cd		

# Light technical data

Beam angle	36 °	
Nominal beam angle	36 °	
Starting time	0.0 s	
Warm-up time (60 %)	0.00 s	
Rated beam angle (half peak value)	36.00 °	

# Dimensions & weight



Diameter	51.0 mm
Length	46.0 mm
Overall length	45.0 mm

Outer bulb	MR51		
Maximum diameter	51.0 mm		
Lifespan			
Nominal lamp life time	5000 h		
Rated lamp life time	5000 h		
Number of switching cycles	125000		
Additional product data			
Base (standard designation)	GU5.3		
Mercury content	0.0 mg		
Mercury-free	Yes		
Capabilities			
Burning position	Any		
Dimmable	Yes		
Certificates & standards			
Energy efficiency class	В		


# Country-specific categorizations

**Energy consumption** 

ILCOS	HRGS//UBIB-35-12-GU5.3-51/36
ILCO3	11KG3//0010-33-12-G03.3-31/30

38 kWh/1000h

# **Light Distribution**



#### Spectral power distribution

#### **LOGISTICAL DATA**

Product code	Product description	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Volume	Gross weight
4050300516639	DECOSTAR 51 PRO 35 W 12 V 36° GU5.3	Shipping carton box 20	238 mm x 122 mm x 106 mm	3.08 dm <sup>3</sup>	836.00 g

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

### **DISCLAIMER**

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.