

PRODUCT DATASHEET

HALOSPOT 48 20 W 12 V 8° GY4

HALOSPOT 48 | Halogen spot lamps with 48 mm aluminum reflector



AREAS OF APPLICATION

- General illumination
- Shops
- Restaurants, hotels and similar prestigious applications
- Offices, public buildings

PRODUCT BENEFITS

- Brilliant accent light
- Cap for reduced glare and ease of handling
- Excellent distribution of light thanks to faceted reflector
- Approved for use in open luminaires (to IEC 60598-1)
- UV filter
- Drastically reduced thermal load in luminaire thanks to aluminum-coated reflector
- Contains no mercury

PRODUCT FEATURES

- Color temperature: 2,800 K
- 100 % dimmable
- Color rendering index R_a : 100
- Diameter: 48 mm

TECHNICAL DATA

Electrical data

Nominal wattage	20.00 W
Nominal voltage	12 V
Rated wattage	20.00 W


Photometrical data

Nominal useful luminous flux 90°	150 lm
Luminous intensity	3100 cd
Rated color temperature	2800 K
Light color (designation)	Warm White
Color rendering index Ra	100
Rated useful luminous flux 90°	150 lm
Rated peak intensity	3100 cd

Light technical data

Beam angle	8.00 °
Nominal beam angle	8.00 °
Starting time	0.0 s
Rated beam angle (half peak value)	8.00 °

Dimensions & weight



Diameter	48.0 mm
Length	38.0 mm
Overall length	36.0 mm
Outer bulb	T9

Lifespan

Nominal lamp life time	4000 h
------------------------	--------

Rated lamp life time	4000 h
Number of switching cycles	100000

Additional product data

Base (standard designation)	GY4
Mercury-free	Yes

Capabilities

Burning position	Any
Dimmable	Yes


Certificates & standards

Energy efficiency class	C
Energy consumption	22 kWh/1000h

Country-specific categorizations

ILCOS	HMGS//UB-20-12-GY4-48/8
--------------	-------------------------

Light Distribution



Spectral power distribution

LOGISTICAL DATA

Product code	Product description	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Volume	Gross weight
--------------	---------------------	------------------------------	--------------------------------------	--------	--------------

4050300003962	HALOSPOT 48 20 W 12 V 8° GY4	Shipping carton box 10	231 mm x 69 mm x 96 mm	1.53 dm ³	253.00 g
4050300407197	HALOSPOT 48 20 W 12 V 8° GY4	Shipping carton box 400	500 mm x 400 mm x 270 mm	54.00 dm ³	4991.00 g

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.