
## Ceiling Lights | 220-240 V | 2xE27 4663



Technical data		
recinical udia		
Installation position	Wall lights - Ceiling	
Installation environment	Indoor	
Lamp cap	2 x E27 Max 46W	
Frequency	50-60 Hz	
Optic	Diff. + Diff. + Diff.	
Light emission direction	downward	
Safety class	1	
IP	IP20	
Glow wire test	850°	
Direct mounting on normally flammable surfaces	Yes	
CE	Yes	
ETL	No	
Induzione	No	
Emergency mode	No	
Motion sensor	No	
Directional	No	
Tilting	No	
Walk-over	No	
Drive-over	No	
Cable included	No	
Resin potting	No	

Finishing diffuser		
Material	Glass	
Colour	transparent	
Finishing mour	ting frame	
<b>Finishing mour</b> Material	ting frame Iron	
	•	

## 

Double emission ceiling lights for indoor application. Compatibility: LED lamp, halogen 46 W, compact fluo 20 W; lamp cap 2xE27.

The diffuser is made of glass; the mounting frame is made of iron, with a chrome finish, processed by means of electroplating. The ingress protection degree is IP20; the total weight is of 7.460 kg.

The device features protection class I and can be wall lights or ceilingmounted.

Illuminotechnical Features		
Luminous flux (source)	4000 lm	
Colour temperature	2500 K	
Colour rendering index	100 Ra	