

PRODUCT DATASHEETDECOSTAR 51 TITAN 20 W 12 V 10° GU5.3

DECOSTAR 51 TITAN | Halogen dichroic reflector lamps with 51 mm diameter



AREAS OF APPLICATION

- General illumination
- Shops
- Restaurants, hotels and similar prestigious applications
- Offices, public buildings

PRODUCT BENEFITS

- Brilliant accent light
- Constant bluish appearance of the light escaping at the back of the reflector
- Dichroic reflector reduces the heat in the light beam by up to 66 %
- Constant luminous intensity and constant color location throughout the lifetime
- Flat clear shield
- Approved for use in open luminaires (to IEC 60598-1)
- UV filter
- Contains no mercury

PRODUCT FEATURES

- Average life: 4,000 h
- 100 % dimmable
- Color rendering index R_a: 100Color temperature: 3,000 K
- Diameter: 51 mm
- Deco cover

TECHNICAL DATA

Electrical data

Nominal wattage	20.00 W
Nominal voltage	12 V
Rated wattage	20.00 W
Power factor λ	1.00


Photometrical data

Nominal useful luminous flux 90°	250 lm
Luminous intensity	5000 cd
Rated color temperature	2900 К
Light color (designation)	Warm White
Color rendering index Ra	100
Lumen main.fact.at end of nom.life time	0.75
Rated useful luminous flux 90°	250 lm
Rated peak intensity	5000 cd

Light technical data

Beam angle	10 °	
Nominal beam angle	10 °	
Starting time	0.0 s	
Warm-up time (60 %)	0.00 s	
Rated beam angle (half peak value)	10.00 °	

Dimensions & weight




Diameter	51.0 mm
Length	46.0 mm
Overall length	45.0 mm
Outer bulb	MR51

Maximum diameter 51.0 mm Lifespan Nominal tamp life time 4000 h Rated lamp life time 4000 h Number of switching cycles 100000 Additional product data Base (standard designation) GU5.3 Mercury content 0.0 mg Mercury-free Yes Capabilities Burning position Any Dimmable Yes Certificates & standards Energy efficiency class Energy consumption 22 kWh/1000h Country-specific categorizations		
Nominal lamp life time 4000 h Rated lamp life time 4000 h Number of switching cycles 100000 Additional product data Base (standard designation) GU5.3 Mercury content 0.0 mg Mercury-free Yes Capabilities Burning position Any Dimmable Yes Certificates & standards Energy efficiency class B Energy consumption 22 kWh/1000h	Maximum diameter	51.0 mm
Nominal lamp life time 4000 h Rated lamp life time 4000 h Number of switching cycles 100000 Additional product data Base (standard designation) GU5.3 Mercury content 0.0 mg Mercury-free Yes Capabilities Burning position Any Dimmable Yes Certificates & standards Energy efficiency class B Energy consumption 22 kWh/1000h		
Rated lamp life time 4000 h Number of switching cycles 100000 Additional product data Base (standard designation) GU5.3 Mercury content 0.0 mg Mercury-free Yes Capabilities Burning position Any Dimmable Yes Certificates & standards Energy efficiency class B Energy consumption 22 kWh/1000h	Lifespan	
Number of switching cycles Additional product data Base (standard designation) Mercury content 0.0 mg Mercury-free Yes Capabilities Burning position Any Dimmable Yes Certificates & standards Energy efficiency class B Energy consumption 100000	Nominal lamp life time	4000 h
Additional product data Base (standard designation) GU5.3 Mercury content 0.0 mg Mercury-free Yes Capabilities Burning position Any Dimmable Yes Certificates & standards Energy efficiency class B Energy consumption 22 kWh/1000h	Rated lamp life time	4000 h
Base (standard designation) Mercury content 0.0 mg Mercury-free Yes Capabilities Burning position Any Dimmable Yes Certificates & standards Energy efficiency class B Energy consumption 22 kWh/1000h	Number of switching cycles	100000
Base (standard designation) Mercury content 0.0 mg Mercury-free Yes Capabilities Burning position Any Dimmable Yes Certificates & standards Energy efficiency class B Energy consumption 22 kWh/1000h		
Mercury content 0.0 mg Mercury-free Yes Capabilities Burning position Any Dimmable Yes Certificates & standards Energy efficiency class B Energy consumption 22 kWh/1000h	Additional product data	
Mercury-free Yes Capabilities Burning position Any Dimmable Yes Certificates & standards Energy efficiency class B Energy consumption 22 kWh/1000h	Base (standard designation)	GU5.3
Capabilities Burning position Any Dimmable Yes Certificates & standards Energy efficiency class B Energy consumption 22 kWh/1000h	Mercury content	0.0 mg
Burning position Any Dimmable Yes Certificates & standards Energy efficiency class B Energy consumption 22 kWh/1000h	Mercury-free	Yes
Burning position Any Dimmable Yes Certificates & standards Energy efficiency class B Energy consumption 22 kWh/1000h		
Dimmable Yes Certificates & standards Energy efficiency class Energy consumption B 22 kWh/1000h	Capabilities	
Certificates & standards Energy efficiency class Energy consumption B 22 kWh/1000h	Burning position	Any
Energy efficiency class B Energy consumption 22 kWh/1000h	Dimmable	Yes
Energy efficiency class B Energy consumption 22 kWh/1000h		
Energy consumption 22 kWh/1000h	Certificates & standards	
	Energy efficiency class	В
Country-specific categorizations	Energy consumption	22 kWh/1000h
Country-specific categorizations		

HRGS//UB-20-12-GU5.3-51/10

ILCOS

Light Distribution



Spectral power distribution

LOGISTICAL DATA

Product code	Product description	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Volume	Gross weight
4050300428635	DECOSTAR 51 TITAN 20 W 12 V 10° GU5.3	Shipping carton box 20	103 mm x 122 mm x 246 mm	3.09 dm ³	836.00 g

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.