

PRODUCT DATASHEETDECOSTAR 51S 35 W 12 V 36° GU5.3

DECOSTAR 51S Standard | Halogen dichroic reflector lamps with 51 mm diameter



AREAS OF APPLICATION

- General illumination
- Entrance lighting
- Workplace lighting
- Kitchen lighting
- Mirror lighting
- Object lighting

PRODUCT BENEFITS

- Brilliant accent light
- Dichroic reflector reduces the heat in the light beam by up to 66 %
- Approved for use in open luminaires (to IEC 60598-1)
- UV filter
- Contains no mercury

PRODUCT FEATURES

- Average life: 4,000 h
- 100 % dimmable
- Color rendering index R_a: 100
- Diameter: 51 mm
- Deco cover

TECHNICAL DATA

Electrical data

Nominal wattage	35.00 W
Nominal voltage	12 V
Rated wattage	35.00 W
Power factor λ	1.00


Photometrical data

Nominal useful luminous flux 90°	430 lm	
Luminous intensity	1000 cd	
Rated color temperature	2900 К	
Light color (designation)	Warm White	
Color rendering index Ra	100	
Lumen main.fact.at end of nom.life time	0.75	
Rated useful luminous flux 90°	430 lm	
Rated peak intensity	1000 cd	

Light technical data

Beam angle	36 °	
Nominal beam angle	36 °	
Starting time	0.0 s	
Warm-up time (60 %)	0.00 s	
Rated beam angle (half peak value)	36.00 °	

Dimensions & weight




Diameter	51.0 mm
Length	46.0 mm
Overall length	46.0 mm
Outer bulb	MR51

Maximum diameter	51.0 mm			
The state of the s	320 11111			
Lifespan				
Nominal lamp life time	2000 h			
Rated lamp life time	2000 h			
Number of switching cycles	100000			
Additional product data				
Base (standard designation)	GU5.3			
Mercury content	0.0 mg			
Mercury-free	Yes			
Capabilities				
Burning position	Any			
Dimmable	Yes			
Certificates & standards				
Energy efficiency class	С			
Energy consumption	38 kWh/1000h			

HRGS//UB-35-12-GU5.3-51/36

ILCOS

Light Distribution



Spectral power distribution

LOGISTICAL DATA

Product code	Product description	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Volume	Gross weight
4050300272634	DECOSTAR 51S 35 W 12 V 36° GU5.3	Shipping carton box 20	201 mm x 123 mm x 148 mm	3.66 dm ³	856.12 g

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.