

PRODUCT DATASHEET HQL 80 W E27

HQL | Mercury vapor lamps for open and enclosed luminaires



AREAS OF APPLICATION

- Factories and workshops
- Industrial installations
- Streets
- Car parks, courtyards
- Pedestrian zones, public squares
- Parks and gardens
- Suitable for use in open and enclosed luminaires
- Outdoor applications only in suitable luminaires



TECHNICAL DATA


Electrical data

Nominal wattage	80.00 W
Rated wattage	80.00 W
Lamp current	0.8 A
Nominal voltage	115 V
Ignition voltage	0.198 kVp

Photometrical data

Rated lamp efficacy (standard condition)	48 lm/W
Rated luminous flux	3800 lm
Color rendering index Ra	50
Color temperature	4100 К
Rated LLMF at 2,000 h	0.88
Rated LLMF at 4,000 h	0.83
Rated LLMF at 6,000 h	0.78
Rated LLMF at 8,000 h	0.75
Rated LLMF at 12,000 h	0.70
Rated LLMF at 16,000 h	0.65

Dimensions & weight



Diameter	71.0 mm 155.0 mm 56.00 g	
Length		
Product weight		

Temperatures & operating conditions

Maximum permitted outer bulb temperature	310 °C
Maximum permitted base edge temperature	210 °C

Lifespan

Rated lamp survival factor at 4,000 h0.97Rated lamp survival factor at 6,000 h0.95Rated lamp survival factor at 8,000 h0.90Rated lamp survival factor at 12,000 h0.75Rated lamp survival factor at 16,000 h0.68Rated lamp survival factor at 20,000 h0.60Lifespan B5024000 hLifespan B508000 h		
Rated lamp survival factor at 6,000 h 0.95 Rated lamp survival factor at 8,000 h 0.90 Rated lamp survival factor at 12,000 h 0.75 Rated lamp survival factor at 16,000 h 0.68 Rated lamp survival factor at 20,000 h 0.60 Lifespan B50 24000 h Lifespan B10 8000 h Lifespan B5 6000 h	Rated lamp survival factor at 2,000 h	0.99
Rated lamp survival factor at 8,000 h0.90Rated lamp survival factor at 12,000 h0.75Rated lamp survival factor at 16,000 h0.68Rated lamp survival factor at 20,000 h0.60Lifespan B5024000 hLifespan B108000 hLifespan B56000 h	Rated lamp survival factor at 4,000 h	0.97
Rated lamp survival factor at 12,000 h 0.75 Rated lamp survival factor at 16,000 h 0.68 Rated lamp survival factor at 20,000 h 0.60 Lifespan B50 24000 h Lifespan B10 8000 h Lifespan B5 6000 h	Rated lamp survival factor at 6,000 h	0.95
Rated lamp survival factor at 16,000 h 0.68 Rated lamp survival factor at 20,000 h 0.60 Lifespan B50 24000 h Lifespan B10 8000 h Lifespan B5 6000 h	Rated lamp survival factor at 8,000 h	0.90
Rated lamp survival factor at 20,000 h 0.60 Lifespan B50 24000 h Lifespan B10 8000 h Lifespan B5 6000 h	Rated lamp survival factor at 12,000 h	0.75
Lifespan B50 24000 h Lifespan B10 8000 h Lifespan B5 6000 h	Rated lamp survival factor at 16,000 h	0.68
Lifespan B10 8000 h Lifespan B5 6000 h	Rated lamp survival factor at 20,000 h	0.60
Lifespan B5 6000 h	Lifespan B50	24000 h
	Lifespan B10	8000 h
Operation mode LLMF/LSF 50 Hz	Lifespan B5	6000 h
	Operation mode LLMF/LSF	50 Hz

Additional product data

Base (standard designation)	E27	
Product remark	As of April 2015 not compliant with ErP directive 245/2009	
Design / version	Coated	
Mercury content	14.6 mg	

Capabilities

Dimmable	No	
Burning position	Any	
Enclosed luminaire required	No	


Certificates & standards

Energy efficiency class	В
Energy consumption	88 kWh/1000h

Country-specific categorizations

ILCOS

Light Distribution



Spectral power distribution

LOGISTICAL DATA

Product code	Product description	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Volume	Gross weight
 4050300012360	HQL 80 W E27	Shipping carton box 40	424 mm x 355 mm x 356 mm	53.59 dm³	3742.57 g

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.