

PRODUCT DATASHEET HALOSTAR STARLITE 90 W 12 V GY6.35

HALOSTAR STARLITE | Low-voltage halogen lamps with pin base



AREAS OF APPLICATION

- General illumination
- Entrance lighting
- Accent lighting
- Lighting for reading
- Garden lighting
- Shops
- Restaurants, hotels and similar prestigious applications
- Offices, public buildings
- Outdoor applications only in suitable luminaires

PRODUCT BENEFITS

- Brilliant accent light
- Incredibly small dimensions for revolutionary new luminaire designs
- Approved for use in open luminaires (to IEC 60598-1)
- Axial filament for optimum directional light
- Special pins for corrosion protection
- UV filter
- Contains no mercury

PRODUCT FEATURES

- Average life: 4,000 h
- 100 % dimmable
- Color rendering index R_a: 100

TECHNICAL DATA

Electrical data

| Nominal wattage | 90.00 W |
|------------------------|---------|
| Nominal voltage | 12 V |
| Rated wattage | 90.00 W |
| Power factor λ | 1.00 |


Photometrical data

| Nominal luminous flux | 1800 lm |
|---|------------|
| Rated color temperature | 3000 К |
| Light color (designation) | Warm White |
| Rated luminous flux | 1800 lm |
| Color rendering index Ra | 100 |
| Lumen main.fact.at end of nom.life time | 0.80 |

Light technical data

| Starting time | 0.0 s |
|---------------------|--------|
| Warm-up time (60 %) | 0.00 s |

Dimensions & weight



| Diameter | 12.0 mm |
|---------------------------|---------|
| Overall length | 44.0 mm |
| Light center length (LCL) | 30.0 mm |
| Length | 44.0 mm |
| Outer bulb | T12 |
| Maximum diameter | 12.0 mm |

Lifespan

| Nominal lamp life time | 4000 h |
|------------------------|--------|
|------------------------|--------|

PRODUCT DATASHEET

| Rated lamp life time | 4000 h |
|----------------------------|--------|
| Number of switching cycles | 100000 |

Additional product data

| Base (standard designation) | GY6.35 |
|-----------------------------|--------|
| Mercury content | 0.0 mg |
| Mercury-free | Yes |

Capabilities

| Burning position | Any |
|------------------|-----|
| Dimmable | Yes |


Certificates & standards

| Energy efficiency class | C |
|-------------------------|--------------|
| Energy consumption | 96 kWh/1000h |

Country-specific categorizations

| ILCOS | HSGST/C/UB-90-12-GY6.35-12/30 |
|-------|-------------------------------|
|-------|-------------------------------|

Light Distribution



Spectral power distribution

LOGISTICAL DATA

| Product code | Product description | Packaging unit (Pieces/Unit) | Dimensions (length x width x height) | Volume | Gross weight |
|---------------|---------------------------------------|---------------------------------|---|----------|--------------|
| 4050300490182 | HALOSTAR STARLITE 90 W 12 V GY6.35 | Shipping carton box 40 | 144 mm x 107 mm x 121 mm | 1.86 dm³ | 250.50 g |

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.