

PRODUCT DATASHEETHALOSTAR STARLITE 75 W 12 V GY6.35

HALOSTAR STARLITE | Low-voltage halogen lamps with pin base



AREAS OF APPLICATION

- General illumination
- Entrance lighting
- Accent lighting
- Lighting for reading
- Garden lighting
- Shops
- Restaurants, hotels and similar prestigious applications
- Offices, public buildings
- Outdoor applications only in suitable luminaires

PRODUCT BENEFITS

- Brilliant accent light
- Incredibly small dimensions for revolutionary new luminaire designs
- Approved for use in open luminaires (to IEC 60598-1)
- Axial filament for optimum directional light
- Special pins for corrosion protection
- UV filter
- Contains no mercury

PRODUCT FEATURES

- Average life: 4,000 h
- 100 % dimmable
- Color rendering index R_a: 100

TECHNICAL DATA

Electrical data

Nominal wattage	75.00 W	
Nominal voltage	12 V	
Rated wattage	75.00 W	
Power factor λ	1.00	


Photometrical data

Nominal luminous flux	1450 lm
Rated color temperature	3000 K
Light color (designation)	Warm White
Rated luminous flux	1450 lm
Color rendering index Ra	100
Lumen main.fact.at end of nom.life time	0.80

Light technical data

Starting time	0.0 s	
Warm-up time (60 %)	0.00 s	

Dimensions & weight



Diameter	12.0 mm
Overall length	44.0 mm
Light center length (LCL)	30.0 mm
Length	44.0 mm
Outer bulb	T12
Maximum diameter	12.0 mm

Lifespan

Nominal lamp life time	4000 h

Rated lamp life time	4000 h	
Number of switching cycles	100000	

Additional product data

Base (standard designation)	GY6.35
Mercury content	0.0 mg
Mercury-free	Yes

Capabilities

Burning position	Any	
Dimmable	Yes	


Certificates & standards

Energy efficiency class	С
Energy consumption	80 kWh/1000h

Country-specific categorizations

ILCOS	HSGST/C/UB-75-12-GY6.35-12/30

Light Distribution



Spectral power distribution

LOGISTICAL DATA

Product code	Product description	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Volume	Gross weight
4050300490151	HALOSTAR STARLITE 75 W 12 V GY6.35	Shipping carton box 40	144 mm x 107 mm x 121 mm	1.86 dm ³	230.00 g

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.