

# 66240CBI

## XENARC COOL BLUE INTENSE | Xenon headlight lamps



## Areas of application

- Headlight

### **Product benefits**

- Exceptionally bright
- Offers high contrast and is now brilliantly blue
- Up to 20 % more light (compared to conventional coated gas discharge lamps)

### **Product features**

- Color temperature: up to 5,500 K
- Blue effect without coating



## Product datasheet

### Technical data


## **Electrical data**


| Power input           | 35 W    |
|-----------------------|---------|
| Nominal voltage       | 85.0 V  |
| Nominal wattage       | 35.00 W |
| Power input tolerance | ±3 %    |
| Test voltage          | 13.5 V  |


## Photometrical data

| Color temperature | 4800 K  |
|-------------------|---------|
| Luminous flux     | 3200 lm |

## Dimensions & weight







| Length         | 77.0 mm |
|----------------|---------|
| Diameter       | 9 mm    |
| Product weight | 16.00 g |

## Lifespan

| Lifespan B3 | 1800 h |
|-------------|--------|
| Lifespan Tc | 2800 h |

## Additional product data

| Base (standard designation) | P32d-2   |  |  |
|-----------------------------|--|--|--|
| Product remark              | Reduced UV emission/For projection headlights/ECE approval and DOT label |  |  |

## **Certificates & standards**

| ECE category | D2S <sup>1)</sup> |
|--------------|-------------------|

## Product datasheet

## **Country specific categorizations**

## Country specific information

| Product code  | METEL code   | SEG-No. | STK-Number | UK Org |
|---------------|--------------|---------|------------|--------|
| 4008321401359 | OSRA66240CBI | -       | -          | -      |

 $<sup>^{1)}</sup>$  To be operated only with approved electronic control gear

## Product datasheet

### Safety advice

XENARC lamp change is recommended to be carried out by a professional.

### Logistical Data

| Product code  | Product description | Packaging unit<br>(Pieces/Unit) | Dimensions (length x width x height) | Volume               | Gross weight |
|---------------|---------------------|---------------------------------|--------------------------------------|----------------------|--------------|
| 4008321401359 | 66240CBI            | Folding carton box<br>1         | 87 mm x 33 mm x<br>33 mm             | 0.09 dm <sup>3</sup> | 25.07 g      |
| 4052899336209 | 66240CBI            | Shipping carton box 4           | 118 mm x - x 97<br>mm                | 1.12 dm³             | 172.00 g     |
| 4052899336216 | 66240CBI            | Shipping carton box 48          | - x - x -                            |                      |              |

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

#### Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.