

# **PRODUCT DATASHEET**DECOSTAR 51 TITAN 35 W 12 V 24° GU5.3

DECOSTAR 51 TITAN | Halogen dichroic reflector lamps with 51 mm diameter



#### **AREAS OF APPLICATION**

- General illumination
- Shops
- Restaurants, hotels and similar prestigious applications
- Offices, public buildings

#### **PRODUCT BENEFITS**

- Brilliant accent light
- Constant bluish appearance of the light escaping at the back of the reflector
- Dichroic reflector reduces the heat in the light beam by up to 66 %
- Constant luminous intensity and constant color location throughout the lifetime
- Flat clear shield
- Approved for use in open luminaires (to IEC 60598-1)
- UV filter
- Contains no mercury

#### **PRODUCT FEATURES**

- Average life: 4,000 h
- 100 % dimmable
- Color rendering index R<sub>a</sub>: 100Color temperature: 3,000 K
- Diameter: 51 mm
- Deco cover

# **TECHNICAL DATA**

### Electrical data

Nominal wattage	35.00 W
Nominal voltage	12 V
Rated wattage	35.00 W
Power factor λ	1.00


# Photometrical data

Nominal useful luminous flux 90°	550 lm		
Luminous intensity	3100 cd		
Rated color temperature	3000 K		
Light color (designation)	Warm White		
Color rendering index Ra	100		
Lumen main.fact.at end of nom.life time	0.75		
Rated useful luminous flux 90°	550 lm		
Rated peak intensity	3100 cd		

# Light technical data

Beam angle	24 °	
Nominal beam angle	24 °	
Starting time	0.0 s	
Warm-up time (60 %)	0.00 s	
Rated beam angle (half peak value)	24.00 °	

# Dimensions & weight



Diameter	51.0 mm
Length	46.0 mm
Overall length	45.0 mm
Outer bulb	MR51


Maximum diameter	51.0 mm	
Lifespan		
Nominal lamp life time	4000 h	
Rated lamp life time	4000 h	
Number of switching cycles	100000	
Additional and an date		
Additional product data		
Base (standard designation)	GU5.3	
Mercury content	0.0 mg	
Mercury-free	Yes	
6		
Capabilities		
Burning position	Any	
Dimmable	Yes	
Certificates & standards		
Energy efficiency class	В	
Energy consumption	38 kWh/1000h	

HRGS//UB-35-12-GU5.3-51/24

Country-specific categorizations

ILCOS

# **Light Distribution**



#### Spectral power distribution

### **LOGISTICAL DATA**

Product code	Product description	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Volume	Gross weight
4050300476414	DECOSTAR 51 TITAN 35 W 12 V 24° GU5.3	Shipping carton box 20	238 mm x 123 mm x 123 mm	3.60 dm <sup>3</sup>	836.00 g

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

## **DISCLAIMER**

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.