

3930

ORIGINAL | Lamps with metal bases



Areas of application

- Position and parking light
- Indicator, brake, fog and reversing lights
- Number plate and side position lights

Product benefits

- OEM Quality
- Wide product range
- Reliable quality

Product features

- Original spare parts

Technical data


Electrical data

Power input	5 W
Nominal voltage	24.0 V
Nominal wattage	4.00 W
Power input tolerance	±10 %
Test voltage	28.0 V

Photometrical data

Luminous flux	35 lm
Luminous flux tolerance	±20 %

Dimensions & weight







IEC 7005-12 DIN 49642 T 12

Length	27.4 mm
Diameter	8.8 mm
Product weight	2.02 g

Lifespan

Lifespan B3	550 h
Lifespan Tc	1000 h

Additional product data

Certificates & standards

ECE category	T4W
--------------	-----

Country specific categorizations

-	
Order reference	3930 4W 24V BA9

Country specific information

Product code	METEL code	SEG-No.	STK number	UK Org
4050300838366	OSRA3930	-	4739924	-

Logistical Data

Product code	Product description	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Volume	Gross weight
4050300838366	3930	Unpacked 1	73 mm x 28 mm x 53 mm	0.11 dm³	3.01 g
4050300525143	3930	Folding carton box 10	46 mm x 29 mm x 112 mm	0.15 dm ³	31.10 g
4008321095695	3930	Shipping carton box 50	148 mm x 115 mm x 55 mm	0.94 dm ³	185.00 g
4050300926001	3930	Blister 2	65 mm x 14 mm x 42 mm	0.04 dm ³	10.33 g
4008321140302	3930	Shipping carton box 20	137 mm x - x 81 mm	1.17 dm ³	128.50 g

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.