



DKM SINGLE-PHASE DIMMABLE TRACK 3MT

Design: Studio Tecnico Ivela



| Product code | Colour |
|--------------|--------------|
| 7520-30-30 | Black |
| 7520-30-31 | White |
| 7520-30-42 | Satin silver |

General Specifications

| | |
|---------------|---|
| Product type | : Tracks |
| Mounting type | : Ceiling - surface, Pendant |
| Description | : The 1-phase dimmable track operates through a + / - polarized signal to manage a wide range of options in the field of light planning. The lighting control systems make it possible to achieve real economies in terms of energetic efficiency, in combination with a scenographic approach to the use of light in different situations, such as show areas, museums, shopping and retail centres. |

| | |
|-----------------------|----------|
| Indoor/outdoor lights | : Indoor |
|-----------------------|----------|

Physical Specifications

| | |
|--------------------|--|
| Load capacity (Kg) | : The DKM tracks can take a 2 Kg. load every 200 mm., with a maximum distance of 800 mm. between the fixing points. For a 10 Kg. load every 200 mm., the maximum fixing distance has to be 400 mm. |
|--------------------|--|


| | |
|----------|------------------------------------|
| Body | : Extruded aluminium, Extruded PVC |
| Finishes | : Extruded painted aluminium |

Electrical Specifications


| | |
|----------------|-------|
| Current (A) | : 16 |
| Glow wire (°C) | : 850 |
| Voltage (V) | : 250 |

Weight and Dimensions

| | |
|-------------|----------|
| Shape | : Square |
| Length (mm) | : 3000 |
| Width (mm) | : 36 |
| Height (mm) | : 33 |




Accessories

| | | | | | | | | | |
|---|--|--|--|--|---|--|---|---|---|
|  |  |  |  |  |  |  |  |  |  |
| 7606-00-30/31 Suspension kit | 7606-06-30/31 Suspension kit | 7655-10-W20/30/31 Inside L joint | 7655-11-W20/30/31 Outside L joint | 7657-10-W20/30/31 X joint | 7654-10-W30/31 Mechanical straight joint | 7656-10-W20/30/31 Right T joint | 7656-11-W20/30/31 Left T joint | 7658-10-W20/30/31 Flexible joint | 7659-00-W20/30/31 Dead end |
|  |  |  |  |  |  |  |  |  |  |
| 7624-00-30/31 Track cover | 7606-05-30/31 Suspension kit | 7606-04-00 Plate | 7625-00-30/31/52 Mechanical adapter | 7607-00-00 Ceiling kit | 7626-00-00 Suspension kit | 7609-00-00 Nut | 7559-00-20/30/31 Electro/mechanical adapter | 7651-10-W20/30/31 Right live-end | 7651-11-W20/30/31 Left live-end |
|  |  |  |  |  | | | | | |
| 7661-10-W20/30/31 Central connector and straight joint | 7617-00-30/31/52 Mechanical adapter with hook | 7618-00-30/31/52 Mechanical adapter with automatic locking | 7660-00-W20/30/31 Mobile joint (on demand) | 7604Q-10-W30/31 Electrical straight joint and with stop | | | | | |

Pictures and Applications

SCHEMA ELETTRICO / WIRING DIAGRAMS



CAPACITÀ DI CARICO / LOAD CAPACITY

