
Aruba

Pendant Luminaires | 220-240 V | stripLED 19 W 700 mA | CRI 80 8931



Technical data	
Туре	Surface
Installation position	Ceiling
Installation environment	Indoor
Light Source	LED
Circuit structure	stripLED
Optics	General Lighting
Light emission direction	downward and upward
Power	19 W
Source lumens	2287 lm
Frequency	60 - 50 Hz
CCT / Tone	3000 K
Colour rendering index	80 Ra
AC / DC	AC
Safety class	1
IP	IP20
Glow wire test	650°
Direct mounting on normally flammable surfaces	Yes
CE	Yes
ETL	No
Fire Rated (BS 476 PT21 compliant)	No
Driver included	Driver
Induction	No
Emergency mode	No
Motion sensor	No
Directional	No
Tilting	No
Walk-over	No
Drive-over	No
Cable included	No
Resin potting	No
Type of light emission	Double emission
Electrostatic discharge protection	No
Surge protection	No

Finishing casin	g	
Material	Iron	
Colour	gold	
Processing	Electroplating	
Finishing diffus	er	
Material	Glass	
Colour	transparent	
Processing	Sandblasting	
Finishing moun	ting frame	
Material	Iron	
Colour	embossed white RAL 9003	



Aruba

Pendant Luminaires | 220-240 V | stripLED 19 W 700 mA | CRI 80 8931

Double emission pendant luminaires for indoor application. The warm white LED light source with a general lighting light distribution is composed of 72 stripled LEDs with CCT of 3000 K and a CRI 80; the source luminous flux is 2287 lm, with a 120.4 lm/W nominal luminous efficacy.

The device body is made of iron and features a gold finish, processed by means of electroplating; the diffuser is made of glass with a sandblasting treatment; the mounting frame is made of iron, with a embossed white ral 9003 finish. The ingress protection degree is IP20;

The total absorbed power is 19 W.

The device features protection class I and can be ceiling-mounted.

Compliant with the EN 60598-1 standard and its specific provisions.

Illuminotechnical Features	
Source lumens	2287 lm
Colour temperature	3000 K
Standard Deviation of Colour Matching	3 Step MacAdam
Colour rendering index	80 Ra
Junction temperature (lighting fixture)	80 °C
Standard Operating Ambient Temperature	25 °C
LED Life / Failure Ratio	
L70 B20 C0 72.5h	