




Ceiling Lights | 220-240 V | stripLED 40 W 700 mA | CRI 80  
8926



| Technical data                                 |                       |
|--|-----------------------|
| Type   | Surface               |
| Installation position                          | Wall lights - Ceiling |
| Installation environment                       | Indoor                |
| Light Source                                   | LED                   |
| Circuit structure                              | stripLED              |
| Optics   | General Lighting      |
| Light emission direction                       | downward and upward   |
| Power  | 40 W                  |
| Source lumens                                  | 4457 lm               |
| Frequency                                      | 50 - 60 Hz            |
| CCT / Tone                                     | 3000 K                |
| Colour rendering index                         | 80 Ra                 |
| AC / DC  | AC                    |
| Safety class                                   | 1                     |
| IP   | IP20                  |
| Glow wire test                                 | 650°                  |
| Direct mounting on normally flammable surfaces | Yes                   |
| CE   | Yes                   |
| ETL  | No                    |
| Fire Rated (BS 476 PT21 compliant)             | No                    |
| Driver included                                | Driver                |
| Induction                                      | No                    |
| Emergency mode                                 | No                    |
| Motion sensor                                  | No                    |
| Directional                                    | No                    |
| Tilting  | No                    |
| Walk-over                                      | No                    |
| Drive-over                                     | No                    |
| Cable included                                 | No                    |
| Resin potting                                  | No                    |
| Type of light emission                         | Double emission       |
| Electrostatic discharge protection             | No                    |
| Surge protection                               | No                    |

| Finishing diffuser |              |
|--------------------|--------------|
| Material           | Glass        |
| Colour             | transparent  |
| Processing         | Sandblasting |

| Finishing mounting frame |                         |
|--------------------------|-------------------------|
| Material                 | Iron                    |
| Colour                   | embossed white RAL 9003 |



Ceiling Lights | 220-240 V | stripLED 40 W 700 mA | CRI 80  
**8926**

Double emission ceiling lights for indoor application. The warm white LED light source with a general lighting light distribution is composed of 56 striplid LEDs with CCT of 3000 K and a CRI 80; the source luminous flux is 4457 lm, with a 111.4 lm/W nominal luminous efficacy.

; the diffuser is made of glass with a sandblasting treatment; the mounting frame is made of iron, with a embossed white ral 9003 finish. The ingress protection degree is IP20;

The total absorbed power is 40 W.

The device features protection class I and can be wall lights or ceiling-mounted.

Compliant with the EN 60598-1 standard and its specific provisions.

| <b>Illuminotechnical Features</b>       |                |
|---|----------------|
| Source lumens                           | 4457 lm        |
| Colour temperature                      | 3000 K         |
| Standard Deviation of Colour Matching   | 3 Step MacAdam |
| Colour rendering index                  | 80 Ra          |
| Junction temperature (lighting fixture) | 80 °C          |
| Standard Operating Ambient Temperature  | 25 °C          |
| <b>LED Life / Failure Ratio</b>         |                |
| L70 B20 C0 72.5h                        |                |