


Perfetto-IN 50 3,5W 2700K

Design: Aria Design Team



IP 43 IK 08



| Product Code | Color |
|--------------|-----------|
| 225-029CN-21 | Mat white |

General specifications

| | |
|----------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Product type | Downlights |
| Mounting type | Ceiling - recessed |
| Indoor/Outdoor light | Indoor |
| Description | Fixed downlight with frosted thermoplastic screen, equipped with COB LED of latest generation. Inner snoot in black thermoplastic material. LED drivers should be ordered separately, the wattage of the fitting changes depending on the selected driver. |
| Applications | Showrooms , Residential , Hospitality , Commercial areas |

Lighting specifications

| | |
|---------------------------------------|----------------------------|
| Lamp description | LED 340lm 3.5W 2700K CRI90 |
| Nominal lumens on thermal regime (lm) | 340 |
| Delivered lumen (lm) | 238 |
| Wattage (W) | 3.5 |
| Color temperature (K) | 2700 |
| CRI | CRI 90 |
| Lamp type | COB LED |
| Average lamp life (h) | L80B10 50.000 |
| Photobiological risk group | RG1 |

Physical specifications

| | |
|---------------------|------------------------------------------|
| Body | Die-cast aluminium |
| Finishing | Polyester painted |
| Reflector | Mirror-metallized thermoplastic material |
| Thermal dissipation | Passive |

Electrical specifications

| | |
|---------------------|----------|
| Driver availability | Separate |
| Driver mounting | Separate |

Optical specifications

| | |
|--------------------|-----------|
| Light distribution | Symmetric |
| Emission | Direct |
| Light beam | 34° |
| Optical notes | |

Weight and dimension

| | |
|------------------------------|------|
| Height (mm) | 50 |
| Diameter (mm) | 50 |
| Cutout diameter (mm) | 43 |
| Recessed depth (mm) | 50 |
| Weight (Kg) | 0.1 |
| False ceiling thickness (mm) | 1-20 |

Accessories



Product Code 28-9022-51S
Name Professional optic device S
Light beam 26 °
Finishing Mirror metallized



Product Code 28-9022-51W
Name Professional optic device W
Light beam 54 °
Finishing Mirror metallized



Product Code 28-4220-100
Name Satined gold baffle



Product Code 28-4200-30
Name Honeycomb
Finishing Black painted



Product Code 28-4227-47
Name Prismatic spread lens

Driver

Product Code 81-02408
Name Driver 350mA
Driver current (mA) 350