


Perfetto-IN 50 6,5W 2700K

DALI

Design: Aria Design Team



IP 43 IK 08



Product Code	Color
225-029CN-21	Mat white

General specifications

Product type	Downlights
Mounting type	Ceiling - recessed
Indoor/Outdoor light	Indoor
Description	Fixed downlight with frosted thermoplastic screen, equipped with COB LED of latest generation. Inner snoot in black thermoplastic material. LED drivers should be ordered separately, the wattage of the fitting changes depending on the selected driver.
Product notes	Max 4 fittings 6,5W can be connected in series to the driver 81-04028 (700mA DALI dimmable)
Applications	Showrooms , Residential , Hospitality , Commercial areas

Lighting specifications

Lamp description	LED 620lm 6.5W 2700K CRI90
Nominal lumens on thermal regime (lm)	620
Delivered lumen (lm)	434
Wattage (W)	6.5
Color temperature (K)	2700
CRI	CRI 90
Lamp type	COB LED
Average lamp life (h)	L80B10 50.000
Photobiological risk group	RG1

Physical specifications

Body	Die-cast aluminium
Finishing	Polyester painted
Reflector	Mirror-metallized thermoplastic material
Thermal dissipation	Passive

Electrical specifications

Driver availability	Separate
Driver mounting	Separate
Dimmable	DALI dimmable

Optical specifications

Light distribution	Symmetric
Emission	Direct
Light beam	34°
Optical notes	

Weight and dimension

Height (mm)	50
Diameter (mm)	50
Cutout diameter (mm)	43
Recessed depth (mm)	50
Weight (Kg)	0.1
False ceiling thickness (mm)	1-20

Accessories



Product Code	28-9022-51S
Name	Professional optic device S
Light beam	26 °
Finishing	Mirror metallized



Product Code	28-9022-51W
Name	Professional optic device W
Light beam	54 °
Finishing	Mirror metallized



Product Code	28-4220-100
Name	Satined gold baffle



Product Code	28-4200-30
Name	Honeycomb
Finishing	Black painted



Product Code	28-4227-47
Name	Prismatic spread lens

Driver

Product Code	81-04028
Name	Driver 700mA dimmable DALI
Description	For a correct installation, please consider a ceiling recessed depth of 200mm.
Driver current (mA)	700