


## Perfetto-IN 40 4,5W 3000K

Design: Aria Design Team



IP 43 IK 07



Product Code	Color
254-209BN-21	Mat white

### General specifications

Product type	Downlights
Mounting type	Ceiling - recessed
Indoor/Outdoor light	Indoor
Description	Fixed downlight with prismatic spread lens, designed for the latest generation of COB LEDs . Inner snoot in black thermoplastic material. LED drivers should be ordered separately for remote installation.
Product notes	Max 2 fittings 4.5W can be connected to the driver 81-04031 (500mA).
Applications	Commercial areas , Showrooms , Residential , Hospitality

### Lighting specifications

Lamp description	LED 500lm 4.5W 3000K CRI90
Nominal lumens on thermal regime (lm)	500
LOR	85
Delivered lumen (lm)	425
Wattage (W)	4.5
Color temperature (K)	3000
CRI	CRI 90
Lamp type	COB LED
Average lamp life (h)	L80B10 50.000
Photobiological risk group	RG1
Unified Glare Rating (U.G.R. <)	19

### Physical specifications

Body	Die-cast aluminium
Finishing	Polyester painted
Thermal dissipation	Passive

### Electrical specifications

Driver availability	Separate
Driver mounting	Separate

### Optical specifications

Light distribution	Symmetric
Emission	Direct
Aiming	Fixed
Light beam	60°
Optical notes	Satined gold snoot code 28-4105-100, white baffle code 28-4105-31.

### Weight and dimension

Height (mm)	45
Diameter (mm)	41
Cutout diameter (mm)	36
Recessed depth (mm)	45
Weight (Kg)	0.1
False ceiling thickness (mm)	1-30

### Accessories

---



Product Code 28-4105-100  
Name Satined gold baffle



Product Code 28-4105-31  
Name White baffle

### Driver

---

Product Code 81-04031  
Name Output 500mA (max 14W) constant current  
Description For a correct installation please consider a ceiling recessed depth of 160mm.  
Driver current (mA) 500