


Perfetto-IN 50 4,5W 2700K

DALI

Design: Aria Design Team



IP 43 IK 08



Product Code	Color
225-029CN-21	Mat white

General specifications

Product type	Downlights
Mounting type	Ceiling - recessed
Indoor/Outdoor light	Indoor
Description	Fixed downlight with frosted thermoplastic screen, equipped with COB LED of latest generation. Inner snoot in black thermoplastic material. LED drivers should be ordered separately, the wattage of the fitting changes depending on the selected driver.
Applications	Showrooms , Residential , Hospitality , Commercial areas

Lighting specifications

Lamp description	LED 470lm 4.5W 2700K CRI90
Nominal lumens on thermal regime (lm)	470
Delivered lumen (lm)	329
Wattage (W)	4.5
Color temperature (K)	2700
CRI	CRI 90
Lamp type	COB LED
Average lamp life (h)	L80B10 50.000
Photobiological risk group	RG1

Physical specifications

Body	Die-cast aluminium
Finishing	Polyester painted
Reflector	Mirror-metallized thermoplastic material
Thermal dissipation	Passive

Electrical specifications

Driver availability	Separate
Driver mounting	Separate
Dimmable	DALI dimmable

Optical specifications

Light distribution	Symmetric
Emission	Direct
Light beam	34°
Optical notes	

Weight and dimension

Height (mm)	50
Diameter (mm)	50
Cutout diameter (mm)	43
Recessed depth (mm)	50
Weight (Kg)	0.1
False ceiling thickness (mm)	1-20

Accessories



Product Code 28-9022-51S
Name Professional optic device S
Light beam 26 °
Finishing Mirror metallized



Product Code 28-9022-51W
Name Professional optic device W
Light beam 54 °
Finishing Mirror metallized



Product Code 28-4220-100
Name Satined gold baffle



Product Code 28-4200-30
Name Honeycomb
Finishing Black painted



Product Code 28-4227-47
Name Prismatic spread lens

Driver

Product Code 81-04026
Name Driver 500mA DALI dimmable
Driver current (mA) 500