


Perfetto-IN 40 with lens 2W 2700K

Design: Aria Design Team



IP 43 IK 07



Product Code	Color
254-219CN-21	Mat white

General specifications

Product type	Downlights
Mounting type	Ceiling - recessed
Indoor/Outdoor light	Indoor
Description	Fixed downlight with no replaceable lens and prismatic spread lens, equipped with LED of latest generation. Inner snoot in black thermoplastic material. LED drivers should be ordered separately for installation through the recessed hole; the wattage of the fitting changes depending on the selected driver.
Product notes	Max 8 fittings (2W) can be connected to the driver 81-04019 (500mA)
Applications	Commercial areas , Showrooms , Residential , Hospitality

Lighting specifications

Lamp description	LED 130lm 2W 2700K CRI90
Nominal lumens on thermal regime (lm)	130
LOR	85
Delivered lumen (lm)	110
Wattage (W)	2
Color temperature (K)	2700
CRI	CRI 90
Lamp type	High Power LED
Average lamp life (h)	L80B10 50.000
Photobiological risk group	RG1
Unified Glare Rating (U.G.R. <)	9

Physical specifications

Body	Die-cast aluminium
Finishing	Polyester painted
Thermal dissipation	Passive

Electrical specifications

Driver availability	Separate
Driver mounting	Separate

Optical specifications

Light distribution	Symmetric
Emission	Accent light
Aiming	Fixed
Light beam	14°
Optical notes	Satined gold snoot code 28-4105-100, white baffle code 28-4105-31

Weight and dimension

Height (mm)	45
Diameter (mm)	41
Cutout diameter (mm)	36
Recessed depth (mm)	45
Weight (Kg)	0.1
False ceiling thickness (mm)	1-30

Accessories



Product Code 28-4105-100
Name Satined gold baffle



Product Code 28-4105-31
Name White baffle

Driver

Product Code 81-04019
Name Driver 500mA (max 20W) constant current
Driver current (mA) 500