



Perfetto-IN 40 4,5W 2700K

Design: Aria Design Team



IP 43 IK 07



| Product Code | Color |
|--------------|-----------|
| 254-209CN-21 | Mat white |

General specifications

| | |
|----------------------|--|
| Product type | Downlights |
| Mounting type | Ceiling - recessed |
| Indoor/Outdoor light | Indoor |
| Description | Fixed downlight with prismatic spread lens, designed for the latest generation of COB LEDs . Inner snoot in black thermoplastic material. LED drivers should be ordered separately installation through the recessed hole. |
| Product notes | Max 4 fittings (4.5W) can be connected to the driver 81-04019 (500mA) |
| Applications | Commercial areas , Showrooms , Residential , Hospitality |

Lighting specifications

| | |
|---------------------------------------|----------------------------|
| Lamp description | LED 470lm 4.5W 2700K CRI90 |
| Nominal lumens on thermal regime (lm) | 470 |
| LOR | 85 |
| Delivered lumen (lm) | 399 |
| Wattage (W) | 4.5 |
| Color temperature (K) | 2700 |
| CRI | CRI 90 |
| Lamp type | COB LED |
| Average lamp life (h) | L80B10 50.000 |
| Photobiological risk group | RG1 |
| Unified Glare Rating (U.G.R. <) | 19 |

Physical specifications

| | |
|---------------------|--------------------|
| Body | Die-cast aluminium |
| Finishing | Polyester painted |
| Thermal dissipation | Passive |

Electrical specifications

| | |
|---------------------|----------|
| Driver availability | Separate |
| Driver mounting | Separate |

Optical specifications

| | |
|--------------------|--|
| Light distribution | Symmetric |
| Emission | Direct |
| Aiming | Fixed |
| Light beam | 60° |
| Optical notes | Satined gold snoot code 28-4105-100, white baffle code 28-4105-31. |

Weight and dimension

| | |
|------------------------------|------|
| Height (mm) | 45 |
| Diameter (mm) | 41 |
| Cutout diameter (mm) | 36 |
| Recessed depth (mm) | 45 |
| Weight (Kg) | 0.1 |
| False ceiling thickness (mm) | 1-30 |

Accessories



Product Code 28-4105-100
Name Satined gold baffle



Product Code 28-4105-31
Name White baffle

Driver

Product Code 81-04019
Name Driver 500mA (max 20W) constant current
Driver current (mA) 500