






Wide range of switches, energy sockets (compliant with national and international standards), data sockets, devices for the management of climate control, comfort, technical alarms signalling, emergency lighting. The Chorus modular devices are available in four colors, glossy white, satin black, painted titanium and glossy ivory and in different modularities, 1/2, 1, 2 and 3 modules. Thanks to the frame supports for rectangular, square and round boxes, the devices allow you to create endless combinations with the range of Chorus plates.

|  |                              |   |                                |
|--|------------------------------|---|--------------------------------|
| Category   | Relay                        | Output contacts                                     | 10 AX 250V ac                  |
| Type   | Latching relay               | Colour  | Titanium                       |
| No. of poles   | 1P                           | Voltage   | 230V ac                        |
| Standard   | EN 60669-1 - EN 60669-2-2    | Frequency   | 50/60 Hz                       |
| Resistance at test voltage                           | 2000 V at 50 Hz for 1 minute | Insulation resistance                               | > 5 MOhm                       |
| Wiring terminals                                     | With screw                   | Prolonged operation switch (no.of position changes) | 40.000 at In 250 V ac cosØ=0,6 |
| Thermo-pressure with ball                            | 125 °C                       | Glow Wire Test                                      | 850 °C                         |
| Terminal grip on cable traction                      | > 50 N                       | Terminal tightening capacity stranded cables (mm2)  | 1x4 / 2x2,5                    |
| Terminal tightening capacity solid cables (mm2)      | 2x2,5                        | No. Chorus modules                                  | 1                              |
| Rated power (AC1)                                    | 2300 VA                      | Rated power (AC15)                                  | 500 VA                         |
| 230V incandescent-halogen lamps                      | 1000 W                       | Fluorescent lamps with electronic ballast           | 400 W                          |
| Fluorescent lamps with compensated ballast           | 360 W                        | CFL lamps   | 200 W                          |
| 230V LED lamps                                       | 200 W                        | Halogen/LED lamps with electronic transformer       | 200 W                          |
| Halogen/LED lamps with electromechanical transformer | 400 W                        | Electrocod  | 140                            |
| Electrocod   | 140                          |   |                                |

### DIMENSIONAL



### TECHNICAL SYMBOLOGY



### STANDARDS/APPROVALS

