


Microperfetto Low-R 9W 2700K

Design: Aria Design Team



IP 20



Product Code	Color
756-679CN-21	Mat white

General specifications

Product type	Semi- recessed surface spotlights
Mounting type	Ceiling - recessed
Indoor/Outdoor light	Indoor
Description	Spotlight with prismatic spread lens and canopy for recessed application, specially developed for high efficiency COB LEDs. Professional optic devices for different beam angles and optical devices for better visual comfort are available on demand. LED drivers should be ordered separately; the wattage of the fittings changes depending on the selected driver.

Applications	Retail , Residential , Hospitality
--------------	------------------------------------

Lighting specifications

Lamp description	LED 1050lm 9W 2700K CRI90
Nominal lumens on thermal regime (lm)	1050
Delivered lumen (lm)	640
Wattage (W)	9
Color temperature (K)	2700
CRI	CRI 90
Lamp type	COB LED
Average lamp life (h)	L80B10 50.000
Photobiological risk group	RG1
Unified Glare Rating (U.G.R. <)	16

Physical specifications

Body	Die-cast aluminium
Finishing	Polyester painted
Reflector	Mirror-metallized thermoplastic material
Thermal dissipation	Passive

Electrical specifications

Driver availability	Separate
Driver mounting	Separate

Optical specifications

Light distribution	Symmetric
Emission	Direct
Orientation	It can rotate up to 330° around the vertical axis and pivot up to 90° upwards.
Light beam	30°

Weight and dimension

Length (mm)	75
Height (mm)	95
Width (mm)	53
Cutout diameter (mm)	55
Recessed depth (mm)	50
Weight (Kg)	0.4

Accessories



Product Code 28-9001-51
Name Professional optic device S
Light beam 16°
Finishing Mirror metallized



Product Code 28-9003-51
Name Professional optic device W
Light beam 45°
Finishing Mirror metallized



Product Code 28-4139-100
Name Satined gold baffle



Product Code 28-4139-31
Name White baffle



Product Code 28-4163-30
Name Honeycomb
Finishing Black painted



Product Code 28-4073-61
Name Frosted glass



Product Code 28-4073-103
Name Elliptical spread lens

Driver

Product Code 81-04009
Name Driver 250mA
Driver current (mA) 250