


# Nanoperfetto-R 3.5W 2700K

## Design: Aria Design Team























755-279CN-21 Mat white

**General specifications** 

Product type Semi-recessed surface spotlights

Mounting type Ceiling - recessed

Mounting location Ceiling Indoor/Outdoor light Indoor

Description Spotlight with prismatic spread lens and canopy for recessed application, specially developed for high efficiency COB LEDs. Professional optics device for better visual

comfort are available on demand. LED drivers should be ordered separately; the wattage of the fittings changes depending on the selected driver.

Showrooms, Retail, Residential, Museums, Hospitality

**Lighting specifications** 

LED 340lm 3.5W 2700K CRI90 Lamp description

340 Nominal lumens on thermal regime

(lm)

Applications

LOR 65.4

222 Delivered lumen (Im) 3.5 Wattage (W)

Color temperature (K) 2700 CRI CRI 90 Lamp type COB LED

L80B10 50.000 Average lamp life (h)

RG1 Photobiological risk group Unified Glare Rating (U.G.R. <) 12

**Physical specifications** 

Body Die-cast aluminium Finishing Polyester painted

Reflector Mirror-metallized thermoplastic material

Thermal dissipation Passive

**Electrical specifications** 

Driver availability Separate Driver mounting Separate

**Optical specifications** 

Light distribution Symmetric Emission Direct

Orientation It can rotate up to 330° around the vertical axis and pivot up to 90° upwards.

Light beam 34

Weight and dimension

Length (mm) 50 71 Height (mm) Width (mm) 36 Cutout diameter (mm) 42 Recessed depth (mm) 50 Weight (Kg) 0.1



#### Accessories









Product Code 28-9022-51S

Name Professional optic device S

Light beam 26°

Finishing Mirror metallized

Product Code 28-9022-51W

Name Professional optic device W

Light beam 54°

Finishing Mirror metallized

Product Code 28-4175-100
Name Satined gold baffle

Product Code 28-4200-30

Name Honeycomb

Finishing Black painted

## Driver

 Product Code
 81-02408

 Name
 Driver 350mA

 Driver current (mA)
 350

# Pictures

