




220-240 V | topLED 23 W 500 mA | CRI 90
8135



Technical data	
Installation position	Ceiling
Installation environment	Indoor
Light Source	LED
Optics	General Lighting
Light emission direction	downward and upward
Power	23 W
Luminous flux (source)	2794 lm
Frequency	60 - 50 Hz
CCT / Tonaltà	3000 K
Colour rendering index	90 Ra
AC / DC	AC
Safety class	1
IP	IP20
Optical compartment IP	IP40
Glow wire test	650°
Direct mounting on normally flammable surfaces	Yes
CE	Yes
ETL	No
Driver included	Yes
Dimmable article	Phase cut
Induzione	No
Emergency mode	No
Motion sensor	No
Directional	No
Tilting	No
Walk-over	No
Drive-over	No
Cable included	No
Resin potting	No

Finishing diffuser

Material	PE
Colour	neutral

Finishing mounting frame

Material	Aluminium
Colour	embossed white RAL 9003
Processing	Coating



220-240 V | topLED 23 W 500 mA | CRI 90
8135

Double emission pendant luminaires for indoor application. The warm white LED light source with a general lighting light distribution is composed of 104 topped LEDs with CCT of 3000 K and a CRI 90; the source luminous flux is 2794 lm, with a 121.5 lm/W nominal luminous efficacy and an operating lifetime (L80) of 80000 hours.

The diffuser is made of pe; the mounting frame is made of aluminium, with a embossed white ral 9003 finish, processed by means of coating. The ingress protection degree is IP20; the total weight is of 2.220 kg. The power supply driver is included in the delivery.

The total absorbed power is 23 W.


The device features protection class I and can be ceiling-mounted.

Illuminotechnical Features

Luminous flux (source)	2794 lm
Colour temperature	3000 K
Standard Deviation of Colour Matching	3 Step MacAdam
Colour rendering index	90 Ra
Life / Failure ratio	L80C0B20



Mr.Magoo_P | Pendant Luminaires | Accessories
8135



Dimmer
PUSH DIM, 220-240V

Code
KIT0026



Dimmer
Bluetooth, 85-240V

Code
KIT0080