





Ceiling Lights | 220-240 V | topLED 73 W 24 V | CRI 85
7442



Technical data	
Installation position	Ceiling
Installation environment	Indoor
Light Source	LED
Optics	General Lighting
Light emission direction	downward
Power	73 W
Luminous flux (source)	5244 lm
Frequency	50 - 60 Hz
CCT / Tonaltà	3000 K
Colour rendering index	85 Ra
Safety class	1
IP	IP20
Glow wire test	850°
Direct mounting on normally flammable surfaces	Yes
CE	Yes
ETL	No
Driver included	Yes
Induzione	No
Emergency mode	No
Motion sensor	No
Directional	No
Tilting	No
Walk-over	No
Drive-over	No
Cable included	No
Resin potting	No
Net weight	12.000 Kg

Finishing casing	
Material	Aluminium
Colour	embossed white RAL 9003
Processing	Coating
Finishing diffuser	
Material	PC
Processing	Sandblasting

Ceiling Lights | 220-240 V | topLED 73 W 24 V | CRI 85 7442

Single emission ceiling lights for indoor application. The warm white LED light source with a general lighting light distribution is composed of 456 topped LEDs with CCT of 3000 K and a CRI 85; the source luminous flux is 5244 lm, with a 71.8 lm/W nominal luminous efficacy and an operating lifetime (L80) of 80000 hours.

The device body is made of aluminium and features a embossed white ral 9003 finish, processed by means of coating; the diffuser is made of PC with a sandblasting treatment. The ingress protection degree is IP20; the total weight is of 12.000 kg. The power supply driver is included in the delivery.

The total absorbed power is 73 W.

The device features protection class I and can be ceiling-mounted.

Illuminotechnical Features	
Light Output Ratio (LOR)	43 %
Luminous flux (source)	5244 lm
Luminaire luminous flux	2301 lm
Consumption	73 W
Luminaire efficacy	31 lm/W
Colour temperature	3000 K
Standard Deviation of Colour Matching	3 Step MacAdam
Colour rendering index	85 Ra

