
## Cubic\_W

## Wall Lights | 220-240 V | 1xG9 6414





| Technical data                                 |                          |  |
|--|--------------------------|--|
| Installation position                          | Wall lights -<br>Ceiling |  |
| Installation environment                       | Indoor                   |  |
| Power  | 1 x 33                   |  |
| Lamp cap                                       | 1 x G9                   |  |
| Frequency                                      | 50-60 Hz                 |  |
| Optic  | Diff. + Diff.            |  |
| Light emission direction                       | frontal                  |  |
| Safety class                                   | 2                        |  |
| IP   | IP44                     |  |
| Glow wire test                                 | 850°                     |  |
| Direct mounting on normally flammable surfaces | Yes                      |  |
| CE   | Yes                      |  |
| ETL  | No                       |  |
| Induzione                                      | No                       |  |
| Emergency mode                                 | No                       |  |
| Directional                                    | No                       |  |
| Tilting  | No                       |  |
| Walk-over                                      | No                       |  |
| Drive-over                                     | No                       |  |
| Cable included                                 | No                       |  |
| Resin potting                                  | No                       |  |

| Finishing casin  | g              |  |
|------------------|----------------|--|
| Material         | Wood           |  |
| Colour           | wenge          |  |
| Finishing diffus | er             |  |
| Material         | Glass          |  |
| Colour           | white          |  |
| Processing       | Silk-screening |  |
| Finishing mour   | ting frame     |  |
| Material         | PC             |  |

transparent

Colour

17.07.2017

•

Single emission wall lights for indoor application. Halogen lamp included 33W, lamp cap 1xG9.

The device body is made of wood and features a wenge finish; the diffuser is made of glass with a silk-screening treatment; the mounting frame is made of PC, with a transparent finish. The ingress protection degree is IP44; the total weight is of 0.260 kg.

The device features protection class II and can be wall lights or ceilingmounted.

| Illuminotechnical Features |        |  |
|----------------------------|--------|--|
| Luminous flux (source)     | 460 lm |  |
| Colour temperature         | 2700 K |  |
| Colour rendering index     | 100 Ra |  |