




Pendant Luminaires | 220-240 V | topLED 47 W 1400 mA | DALI | CRI 90  
8038



Technical data	
Installation position	Ceiling
Installation environment	Indoor
Light Source	LED
Optics	General Lighting
Light emission direction	downward and upward
Power	47 W
Luminous flux (source)	5685 lm
Frequency	60 - 50 Hz
CCT / Tonalità	3000 K
Colour rendering index	90 Ra
Safety class	1
IP	IP20
Optical compartment IP	IP40
Glow wire test	650°
Direct mounting on normally flammable surfaces	Yes
CE	Yes
ETL	No
Driver included	Yes
Dimmable article	DALI
Induzione	No
Emergency mode	No
Motion sensor	No
Directional	No
Tilting	No
Walk-over	No
Drive-over	No
Cable included	No
Resin potting	No

Finishing casing	
Material	Aluminium
Colour	translucent

Finishing diffuser	
Material	PMMA
Colour	transparent
Processing	Laser engravings

Finishing mounting frame	
Material	Aluminium
Colour	translucent

Pendant Luminaires | 220-240 V | topLED 47 W 1400 mA | DALI | CRI 90  
8038

Double emission pendant luminaires for indoor application. The warm white LED light source with a general lighting light distribution is composed of 105 topped LEDs with CCT of 3000 K and a CRI 90; the source luminous flux is 5685 lm, with a 121.0 lm/W nominal luminous efficacy and an operating lifetime (L80) of 80000 hours.

The device body is made of aluminium and features a translucent finish; the diffuser is made of pmma with a laser engravings treatment; the mounting frame is made of aluminium, with a translucent finish. The ingress protection degree is IP20; The power supply driver is included in the delivery.


The total absorbed power is 47 W.

The device features protection class I and can be ceiling-mounted.

Illuminotechnical Features	
Light Output Ratio (LOR)	64 %
Luminous flux (source)	5685 lm
Luminaire luminous flux	3649 lm
Consumption	47 W
Luminaire efficacy	77 lm/W
Colour temperature	3000 K
Standard Deviation of Colour Matching	3 Step MacAdam
Colour rendering index	90 Ra
Life / Failure ratio	L80C0B20

UGR	
X=4H   Y=8H	S=0.25H
Reflection factor	70/50/20
UGR transversal	< 22
UGR axial	< 19

OPTICAL	
Light distribution simmetry	Asymmetrical
Ottica C0/C180	180°
Ottica C90/C270	163°





Opti-Line | Pendant Luminaires | Accessories  
**8038**



Dimmer  
Bluetooth, 220-240V

**Code**  
KIT0079