
### Ceiling Lights | 220-240 V | topLED 30 W 1000 mA | CRI 90 8607





Technical data	
Installation position	Ceiling
Installation environment	Indoor
Light Source	LED
Optics	General Lighting
Light emission direction	downward
Power	30 W
Luminous flux (source)	4042 lm
Frequency	60 - 50 Hz
CCT / Tonalità	3000 K
Colour rendering index	90 Ra
Safety class	1
IP	IP40
Glow wire test	850°
Direct mounting on normally flammable surfaces	Yes
CE	Yes
ETL	No
Driver included	Yes
Dimmable article	Phase cut
Induzione	No
Emergency mode	No
Motion sensor	No
Directional	No
Tilting	No
Walk-over	No
Drive-over	No
Cable included	No
Resin potting	No



Finishing casing	
Material	Iron
Colour	Rose Gold
Processing	Electroplating

## Finishing diffuser Material PC Colour opaline

### Hinomaru\_S


Double emission ceiling lights for indoor application. The warm white LED light source with a general lighting light distribution is composed of 70 topled LEDs with CCT of 3000 K and a CRI 90; the source luminous flux is 4042 lm, with a 134.7 lm/W nominal luminous efficacy and an operating lifetime (L80) of 80000 hours.

The device body is made of iron and features a rose gold finish, processed by means of electroplating; the diffuser is made of PC. The ingress protection degree is IP40; The power supply driver is included in the delivery.

The total absorbed power is 30 W.

The device features protection class I and can be ceiling-mounted.

Illuminotechnical Features	
Light Output Ratio (LOR)	51 %
Luminous flux (source)	4042 lm
Luminaire luminous flux	2100 lm
Consumption	30 W
Luminaire efficacy	70 lm/W
Colour temperature	3000 K
Standard Deviation of Colour Matching	3 Step MacAdam
Colour rendering index	90 Ra
Life / Failure ratio	L80C0B20
UGR	
X=4H   Y=8H	S=0.25H
Reflection factor	70/50/20
UGR transversal	< 22
UGR axial	< 22
OPTICAL	
Light distribution simmetry	Symmetrical
Ottica C0/C180	123°



1.91 1.86	E(0°) E(C90) E(C0)	62.4° 61.7°	2567 128 137
3.83 3.71	E(0°) E(C90) E(C0)	62.4° 61.7°	642 32 34
5.74 5.57	E(0°) E(C90) E(C0)	62.4° 61.7°	285 14 15
7.65 7.43	E(0°) E(C90) E(C0)	62.4° 61.7°	160 8 9
9.56 9.29	E(0°) E(C90) E(C0)	62.4° 61.7°	103 5 5
11.48 11.14	E(0°) E(C90) E(C0)	62.4° 61.7°	71 4 4
	3.83 3.71 5.74 5.57 7.65 7.43 9.56 9.29	$\begin{array}{c c} 1.91 \\ 1.86 \\ \hline E(0^{\circ}) \\ E(0) \\ \hline E(0) \hline \hline E(0) \\ \hline E(0) \\ \hline E(0) \hline \hline E(0$	$\begin{array}{c cccc} 1.91 \\ 1.86 \\ \hline \\ E(C0) & 61.7^{\circ} \\ \hline \\ \hline \\ \hline \\ \hline \\ \hline \\ \hline \\ 9.56 \\ 9.29 \\ \hline \\ 11.48 \\ 11.14 \\ \hline \\ \hline \\ E(C0) & 62.4^{\circ} \\ \hline \\ E(C0) & 61.7^{\circ} \\ \hline \\ \hline \\ E(C0) & 61.7^{\circ} \\ \hline \\ \hline \\ E(C0) & 62.4^{\circ} \\ \hline \\ E(C0) & 61.7^{\circ} \\ \hline \\ $

C0/C180 (Half-peak divergence: 123.4°) C90/C270 (Half-peak divergence: 124.8°)

# 123°

### Hinomaru\_S

#### Hinomaru\_S | Ceiling Lights | Accessories 8607

DINUY DINUY 200-5050 (C	Dimmer PUSH DIM, 220-240V	Code KIT0026
Casangi	Dimmer	Code
I I I I I I I I I I I I I I I I I I I	Bluetooth, 85-240V	KIT0080