
Wall Lights | 220-240 V | 1xG9 6412



Technical data		
Installation position	Wall lights - Ceiling	
Installation environment	Indoor	
Power	1 x 33	
Lamp cap	1 x G9	
Frequency	50-60 Hz	
Optic	Diff. + Diff.	
Light emission direction	frontal	
Safety class	2	
IP	IP44	
Glow wire test	850°	
Direct mounting on normally flammable surfaces	Yes	
CE	Yes	
ETL	No	
Induzione	No	
Emergency mode	No	
Directional	No	
Tilting	No	
Walk-over	No	
Drive-over	No	
Cable included	No	
Resin potting	No	



Finishing casing		
Material	Glass	
Colour	black	
Finishing diffus	er	
Material	Glass	
Colour	white	
Processing	Silk-screening	
Finishing mour	ting frame	
Material	PC	

transparent

Colour

Wall Lights | 220-240 V | 1xG9 6412

Single emission wall lights for indoor application. Halogen lamp included 33W, lamp cap 1xG9.

The device body is made of glass and features a black finish; the diffuser is made of glass with a silk-screening treatment; the mounting frame is made of PC, with a transparent finish. The ingress protection degree is IP44; the total weight is of 0.260 kg.

The device features protection class II and can be wall lights or ceilingmounted.

Illuminotechnical Features		
Luminous flux (source)	460 lm	
Colour temperature	2700 K	
Colour rendering index	100 Ra	