




Ceiling Lights | 220-240 V | topLED 23 W 500 mA | DALI | CRI 90
8006N



Technical data	
Installation position	Ceiling
Installation environment	Indoor
Light Source	LED
Optics	General Lighting
Light emission direction	downward
Power	23 W
Luminous flux (source)	2914 lm
Frequency	50 - 60 Hz
CCT / Tonaltà	4000 K
Colour rendering index	90 Ra
Safety class	1
IP	IP40
Glow wire test	650°
Direct mounting on normally flammable surfaces	Yes
CE	Yes
ETL	No
Driver included	Yes
Dimmable article	DALI
Induzione	No
Emergency mode	No
Motion sensor	No
Directional	No
Tilting	No
Walk-over	No
Drive-over	No
Cable included	No
Resin potting	No

Finishing diffuser	
Material	PE
Colour	neutral

Finishing mounting frame	
Material	Aluminium
Colour	embossed white RAL 9003
Processing	Coating



Ceiling Lights | 220-240 V | topLED 23 W 500 mA | DALI | CRI 90
8006N

Double emission ceiling lights for indoor application. The warm white LED light source with a general lighting light distribution is composed of 104 topLED LEDs with CCT of 4000 K and a CRI 90; the source luminous flux is 2914 lm, with a 126.7 lm/W nominal luminous efficacy and an operating lifetime (L80) of 80000 hours.

The diffuser is made of pe; the mounting frame is made of aluminium, with a embossed white ral 9003 finish, processed by means of coating. The ingress protection degree is IP40; the total weight is of 2.54 kg. The power supply driver is included in the delivery.

The total absorbed power is 23 W.

The device features protection class I and can be ceiling-mounted.

Illuminotechnical Features

Luminous flux (source)	2914 lm
Colour temperature	4000 K
Standard Deviation of Colour Matching	3 Step MacAdam
Colour rendering index	90 Ra
Life / Failure ratio	L80C0B20 80H