




Ceiling Lights | 220-240 V | topLED 32 W | DALI | CRI 90
8008N



| Technical data | |
|--|---------------------|
| Installation position | Ceiling |
| Installation environment | Indoor |
| Light Source | LED |
| Optics | General Lighting |
| Light emission direction | downward and upward |
| Power | 32 W |
| Luminous flux (source) | 4097 lm |
| Frequency | 50 - 60 Hz |
| CCT / Tonaltà | 4000 K |
| Colour rendering index | 90 Ra |
| AC / DC | AC |
| Safety class | 1 |
| IP | IP40 |
| Glow wire test | 650° |
| Direct mounting on normally flammable surfaces | Yes |
| CE | Yes |
| ETL | No |
| Driver included | Yes |
| Dimmable article | DALI |
| Induzione | No |
| Emergency mode | No |
| Motion sensor | No |
| Directional | No |
| Tilting | No |
| Walk-over | No |
| Drive-over | No |
| Cable included | No |
| Resin potting | No |

| Finishing diffuser | |
|--------------------|---------|
| Material | PE |
| Colour | neutral |

| Finishing mounting frame | |
|--------------------------|-------------------------|
| Material | Aluminium |
| Colour | embossed white RAL 9003 |
| Processing | Coating |



Ceiling Lights | 220-240 V | topLED 32 W | DALI | CRI 90
8008N

Double emission ceiling lights for indoor application. The warm white LED light source with a general lighting light distribution is composed of 156 topLED LEDs with CCT of 4000 K and a CRI 90; the source luminous flux is 4097 lm, with a 128.0 lm/W nominal luminous efficacy and an operating lifetime (L80) of 80000 hours.

The diffuser is made of pe; the mounting frame is made of aluminium, with a embossed white ral 9003 finish, processed by means of coating. The ingress protection degree is IP40; the total weight is of 3.950 kg. The power supply driver is included in the delivery.

The total absorbed power is 32 W.

The device features protection class I and can be ceiling-mounted.

Illuminotechnical Features

| | |
|---------------------------------------|----------------|
| Luminous flux (source) | 4097 lm |
| Colour temperature | 4000 K |
| Standard Deviation of Colour Matching | 3 Step MacAdam |
| Colour rendering index | 90 Ra |
| Life / Failure ratio | L80C0B20 80H |