

Wall Lights | 220-240 V | 2xG9 **3276**














| Technical data | |
|--|------------------|
| Installation position | Wall lights |
| Installation environment | Indoor |
| Power | 2 x 33 W |
| Lamp cap | 2 x G9 |
| Frequency | 50-60 Hz |
| Optics | General Lighting |
| Light emission direction | frontal |
| Safety class | 2 |
| IP | IP44 |
| Glow wire test | 850° |
| Direct mounting on normally flammable surfaces | Yes |
| CE | Yes |
| ETL | No |
| Induzione | No |
| Emergency mode | No |
| Motion sensor | No |
| Directional | No |
| Tilting | No |
| Walk-over | No |
| Drive-over | No |
| Cable included | No |
| Resin potting | No |
| Net weight | 0.455 Kg |

| Finishing casing | |
|--------------------|----------------|
| Materiale lega | Iron |
| Colour | chrome |
| Processing | Electroplating |
| | |
| Finishing diffuser | |
| Materiale lega | Glass |
| Colour | white |
| Processing | Sandblasting |
| | |

Fotis_fix



Wall Lights | 220-240 V | 2xG9 **3276**

Double emission wall lights for indoor application. Halogen lamp included 33W, lamp cap 2xG9.

The device body is made of iron and features a chrome finish, processed by means of electroplating; the diffuser is made of glass with a sandblasting treatment. The ingress protection degree is IP44; the total weight is of 0.455 kg.

The device features protection class II and can be wall lights-mounted.

| Illuminotechnical Features | | |
|----------------------------|--------|--|
| Luminous flux (source) | 920 lm | |
| Colour temperature | 2700 K | |
| Colour rendering index | 100 Ra | |