

Product code	Color
243-250AN-21	Mat white
243-250AN-52	Silver

General Specifications

Product type	: Downlights
Mounting type	: Ceiling - recessed
Description	: Fixed downlight for diffused lighting designed for the last generation of COB LEDs. LED drivers should be ordered separately, the wattage of the fittings changes depending on the selected driver. Protection rating IP44.
Indoor/outdoor lights	: Indoor
Applications	: Accommodation facilities, Retail ,Shopping centres, Showrooms

Lighting specifications

Average lamp life (h)	: L80B10 50.000
Lamp description	: LED 5000lm 38W 4000K
Nominal lumens on thermal regime	: 5000
Efficiency L.O.R. (%)	: 86,0
Delivered lumens (lm)	: 4300
Lamp wattage (W)	: 38
Color temperature (K)	: 4000

Physical Specifications

Body	: Die-cast aluminium
Finishes	: Polyester painted
Reflector	: Mirror-metallized thermoplastic material
Closing Screen	: Tempered safety glass 4 mm
Thermal Dissipation	: Passive
Ring	: Die-cast aluminium polyester painted

Electrical Specifications

Glow wire (°C)	: 850
Driver	: Separate item
Driver mounting	: Remote


Weight and Dimensions

Shape	: Round
External diameter (mm)	: 140
False ceiling thickness (mm)	: 1-30
Height (mm)	: 140
Cutout shape	: Round
Cutout Diameter (mm)	: 126
Recessed depth (mm)	: 150
Weight (Kg)	: 0.7


Optical Specifications

Aiming	: Fixed
Light distribution	: Symmetric
Light emission	: Direct
Light beam	: 60°

ACCESSORIES




Product Code : 28-3403-21/52
 Name : Square frame with clear glass
 Finish : Polyester painted
 Shape : Square




Product Code : 98-13380-61
 Name : Sandblasted glass
 Shape : Round

Drivers



Product Code : 81-04014
 Name : Driver 1050mA DALI dimmable
 description : Driver 1050mA DALI dimmable.

Lamps

Lamp categories	Lamp type	Lamp wattage (W)	Nominal lumens on thermal regime (lm)	Color temperature (K)	Color rendering (CRI)
 LED	COB LED	38	5000	4000	85

Pictures and Applications

