
## Wall Lights | 220-240 V | 1xGU10 6614





| Technical data                                 |                  |
|--|------------------|
| Installation position                          | Wall lights      |
| Installation environment                       | Indoor           |
| Lamp cap                                       | 1 x GU10 Max     |
| Frequency                                      | 50-60 Hz         |
| Optics   | General Lighting |
| Light emission direction                       | downward         |
| Safety class                                   | 1                |
| IP   | IP20             |
| Glow wire test                                 | 850°             |
| Direct mounting on normally flammable surfaces | Yes              |
| CE   | Yes              |
| ETL  | No               |
| Induzione                                      | No               |
| Emergency mode                                 | No               |
| Motion sensor                                  | No               |
| Directional                                    | Yes              |
| Tilting  | No               |
| Walk-over                                      | No               |
| Drive-over                                     | No               |
| Cable included                                 | No               |
| Resin potting                                  | No               |
| Net weight                                     | 0.086 Kg         |
|  |                  |

| Finishing casing |         |  |
|------------------|---------|--|
| Materiale lega   | Iron    |  |
| Processing       | Coating |  |

## Wall Lights | 220-240 V | 1xGU10 6614

Single emission wall lights for indoor application. Compatibility: LED lamp, halogen 42 W; lamp cap 1xGU10.

The device body is made of iron, processed by means of coating. The ingress protection degree is IP20; the total weight is of 0.086 kg.

The device features protection class I and can be wall lights-mounted.

| Illuminotechnical Features |        |
|----------------------------|--------|
| Luminous flux (source)     | 300 lm |
| Colour temperature         | 2800 K |
| Colour rendering index     | 100 Ra |