

Product code	Color
259-200AN-21	Mat white

### General Specifications

Product type	: Downlights
Mounting type	: Ceiling - recessed
Description	: Fixed downlight designed for the last generation of COB LEDs, with a shallow depth. LED drivers should be ordered separately, the wattage of the fittings changes depending on the selected driver. Protection rating IP43. Low glare levels UGR < 19 (Unified Glare Rating).
Indoor/outdoor lights	: Indoor
Applications	: Offices, Retail , Shopping centres

### Lighting specifications

Average lamp life (h)	: L80B10 50.000
Lamp description	: LED 3200lm 26W 4000K
Nominal lumens on thermal regime	: 3200
Efficiency L.O.R. (%)	: 89
Delivered lumens (lm)	: 2848
Lamp wattage (W)	: 26
Color temperature (K)	: 4000

### Physical Specifications

Body	: Die-cast aluminium
Finishes	: Polyester painted
Reflector	: Mirror-metallized thermoplastic material
Closing Screen	: Clear polycarbonate
Thermal Dissipation	: Passive
Ring	: Die-cast aluminium

### Electrical Specifications

Glow wire (°C)	: 850
Driver	: Separate item
Driver mounting	: Remote


### Weight and Dimensions

Shape	: Round
False ceiling thickness (mm)	: 1-30
Length (mm)	: 117
Width (mm)	: 117
Height (mm)	: 73
Cutout shape	: Round
Cutout Diameter (mm)	: 110
Recessed depth (mm)	: 73
Weight (Kg)	: 0.7


### Optical Specifications

Aiming	: Fixed
Light distribution	: Symmetric
Light emission	: Direct
Light beam	: 55°
Note	: 12°, 30° (mirror metallized), 70° (white) optics are available on demand.
Unified Glare Rating (U.G.R.)	: <19 - except for 70° optic

## Drivers



Product Code : 81-04012  
 Name : Driver 700mA  
 description : Driver 700mA

Lamps	Lamp categories	Lamp type	Lamp wattage (W)	Nominal lumens on thermal regime (lm)	Color temperature (K)	Color rendering (CRI)
	LED	COB LED	26	3200	4000	85

## Pictures and Applications

