

Product code	Color
264-250-73	White/black baffle

### General Specifications

Product type	: Downlights
Mounting type	: Ceiling - recessed
Description	: Fixed downlight for both accent and diffused lighting, designed for COB LEDs, featuring a rearward optic for a high visual comfort. Inner snoot in black thermoplastic material. LED driver and cable gland included. High protection rating IP66.
Indoor/outdoor lights	: Indoor
Applications	: Hospitality, Residential

### Lighting specifications

Average lamp life (h)	: L80B10 50.000
Lamp description	: LED 1470lm 12W 3000K CRI 90
Nominal lumens on thermal regime	: 1470
Efficiency L.O.R. (%)	: 56
Delivered lumens (lm)	: 824
Lamp wattage (W)	: 12
Color temperature (K)	: 3000

### Physical Specifications

Body	: Die-cast aluminium
Finishes	: Polyester painted
Reflector	: Mirror-metallized thermoplastic material
Closing Screen	: Clear thermoplastic material
Thermal Dissipation	: Passive

### Electrical Specifications

Glow wire (°C)	: 850
Driver	: Included
Driver mounting	: Remote
Voltage (V)	: 220/240
Frequency (Hz)	: 50/60

### Weight and Dimensions

Shape	: Round
External diameter (mm)	: 92
False ceiling thickness (mm)	: 1-30
Height (mm)	: 95
Cutout shape	: Round
Cutout Diameter (mm)	: 70
Recessed depth (mm)	: 95
Weight (Kg)	: 0.7

### Optical Specifications

Aiming	: Fixed
Light distribution	: Symmetric
Light emission	: Direct
Light beam	: 26°
Note	: 45° (mirror metallized), 65° (white) optics are available on demand.
Unified Glare Rating (U.G.R.)	: <5


## ACCESSORIES



Product Code : 28-3868-31  
 Name : Professional optic device 65°  
 Finish : White  
 Beam : 65°  
 Shape : Round



Product Code : 28-3868-51  
 Name : Professional optic device 45°  
 Finish : Mirror metallized  
 Beam : 45°  
 Shape : Round

Lamps	Lamp categories	Lamp type	Lamp wattage (W)	Nominal lumens on thermal regime (lm)	Color temperature (K)	Color rendering (CRI)
	LED	COB LED	12	1470	3000	90