

# GUELL MICRO KIT S/EW




<b>Part number</b>	3101183
<b>Lampholder:</b>	LED
<b>Light Source:</b>	LED
<b>Wattage:</b>	10 W
<b>Finish:</b>	AN-96 / Anthracite gray / Textured
<b>Insulation class:</b>	I
<b>Degree of protection:</b>	IP 66
<b>IK-J-xxIP:</b>	IK06 1J xx3
<b>CRI:</b>	80
<b>Kelvin:</b>	4000
<b>Power factor:</b>	COSφ ≥ 0,9
<b>Optic:</b>	SYMMETRIC EXTRA WIDE REFLECTOR
<b>Lightsource lumen output:</b>	1485 lm
<b>Luminaire lumen output:</b>	634 lm
<b>L:</b>	L70
<b>B:</b>	B10
<b>Lifetime:</b>	35000 h
<b>Ta MIN luminaire:</b>	-20°
<b>Ta MAX luminaire:</b>	25°




## Description

- LED floodlight for indoor and outdoor lighting, comprising:
- Painted, die-cast aluminium housing, in compact size.
  - Extra-clear flat tempered glass diffuser with internal screen printing
  - Waterproof cable gland M16x1.5 for cables Ø 5- Ø 10 mm
  - Mains voltage 220-240V 50/60Hz LED module protected against surges up to 500V
  - Stainless steel external screws
  - Painted steel bracket
  - GUELL MICRO KIT models are equipped with a technopolymer peg and 3 metres of H05RN-F 3G1 mm<sup>2</sup> cable

## PHOTOMETRIC DATA



## TECHNICAL DRAWINGS



## GUELL MICRO



310495  
Connection Kit Y 3-way D.14-17mm  
IP68



310496  
Connection Kit Y 3-way D.7-10.5mm  
IP68



310513  
Connection Kit D.7-10.5mm IP68.