

GUELL 4 A/W




Part number	06210394
Lampholder:	LED
Light Source:	LED
Wattage:	430 W
Finish:	GR-94 / Metallic grey / Textured
Insulation class:	I
Degree of protection:	IP 66
IK-J-xxIP:	IK07 3J xx5
CRI:	80
Kelvin:	4000
Power factor:	COS ϕ \geq 0,9
Optic:	Asymmetric Wide Reflector
Lightsource lumen output:	58452 lm
Luminaire lumen output:	46372 lm
L:	L70
B:	B10
Lifetime:	130000 h
Ta MIN luminaire:	-30°
Ta MAX luminaire:	30°




Description

- LED floodlight for indoor and outdoor lighting, comprising:
- Die-cast aluminium housing chemically pre-treated and painted with polyester powder coating
 - Flat extra clear tempered glass diffuser
 - Very high performance asymmetrical reflector made of 99.99% plated aluminium, polished, oxidised and free of iridescence
 - Anti-ageing silicone gasket
 - Electrical connection box in black technopolymer
 - Cable gland for cables \varnothing 7 - \varnothing 17 mm
 - Dimmable driver 1-10 V ballast
 - Stainless steel external screws
 - Fully integrated stainless steel aluminium spring clips
 - Steel bracket, hot galvanised and painted in polyester powder
 - Cataphoresis and polyester powder coated steel sheet gear housing

PHOTOMETRIC DATA



TECHNICAL DRAWINGS




GUELL 4 A/W - S/W



14465794
Vetro soft GUELL 4

GUELL 4



14452702
Protective grid



14452894
Cover