

GUELL 3 A50/W




Part number	306114
Lampholder:	LED
Light Source:	LED
Wattage:	305 W
Finish:	GR-94 / Metallic grey / Textured
Insulation class:	I
Degree of protection:	IP 66
IK-J-xxIP:	IK07 3J xx5
CRI:	80
Kelvin:	4000
Power factor:	COS ϕ \geq 0,9
Optic:	Asymmetric Wide Reflector
Lightsource lumen output:	48341 lm
Luminaire lumen output:	35814 lm
L:	L80
B:	B10
Lifetime:	55000 h




Description

- LED floodlight for indoor and outdoor lighting, comprising:
- Die-cast aluminium housing chemically pre-treated and painted with polyester powder coating
 - Flat extra clear tempered glass diffuser
 - Very high performance reflectors made of 99.99% plated aluminium, polished, oxidised and free of iridescence
 - Anti-ageing silicone gasket
 - Cable gland M20x1.5 for cables \varnothing 10- \varnothing 14 mm
 - LED modules and reflectors specifically studied for settings that require highly asymmetrical light distribution.
 - Stainless steel external screws
 - Fully integrated stainless steel aluminium spring clips
 - Powder coated steel bracket

PHOTOMETRIC DATA




TECHNICAL DRAWINGS



GUELL 3




14452894
Cover



14452702
Protective grid




14453994
Wall mount support 1000 mm



14453794
Single pole top support GUELL 3 for poles Ø 60-76 mm/Ø 2.36"-2.99".



14453894
Double pole top support GUELL 3 for poles Ø 60-76 mm/Ø 2.36"-2.99"



14461104
GUELL 3 strengthening bracket.
Suitable for one floodlight single point fixing M10 screw in centre of the bracket.