

## GUELL 4 S/W




<b>Part number</b>	06210094
<b>Lampholder:</b>	LED
<b>Light Source:</b>	LED
<b>Wattage:</b>	430 W
<b>Finish:</b>	GR-94 / Metallic grey / Textured
<b>Insulation class:</b>	I
<b>Degree of protection:</b>	IP 66
<b>IK-J-xxIP:</b>	IK07 3J xx5
<b>CRI:</b>	80
<b>Kelvin:</b>	4000
<b>Power factor:</b>	COS $\phi$ $\geq$ 0,9
<b>Optic:</b>	SYMMETRIC WIDE REFLECTOR
<b>Lightsource lumen output:</b>	58452 lm
<b>Luminaire lumen output:</b>	50573 lm
<b>L:</b>	L70
<b>B:</b>	B10
<b>Lifetime:</b>	130000 h
<b>Ta MIN luminaire:</b>	-30°
<b>Ta MAX luminaire:</b>	30°




### Description

- LED floodlight for indoor and outdoor lighting, comprising:
- Die-cast aluminium housing chemically pre-treated and painted with polyester powder coating
  - Flat extra clear tempered glass diffuser
  - Very high performance symmetrical reflector made of 99.99% plated aluminium, polished, oxidised and free of iridescence
  - Anti-ageing silicone gasket
  - Electrical connection box in black technopolymer
  - Cable gland for cables  $\varnothing$  7 -  $\varnothing$  17 mm
  - Dimmable driver 1-10 V ballast
  - Stainless steel external screws
  - Fully integrated stainless steel aluminium spring clips
  - Steel bracket, hot galvanised and painted in polyester powder
  - Cataphoresis and polyester powder coated steel sheet gear housing

### PHOTOMETRIC DATA



### TECHNICAL DRAWINGS




## GUELL 4 A/W - S/W



14465794  
Vetro soft GUELL 4

## GUELL 4



14452702  
Protective grid



14452894  
Cover