




Wall Lights | 220-240 V | topLED 14 W 350 mA | CRI 80
7908



401

| Technical data | |
|--|------------------|
| Type | Surface |
| Installation position | Wall lights |
| Installation environment | Indoor |
| Light Source | LED |
| Optics | General Lighting |
| Light emission direction | downward |
| Power | 14 W |
| Luminous flux (source) | 1449 lm |
| Frequency | 50 - 60 Hz |
| CCT / Tone | 3000 K |
| Colour rendering index | 80 Ra |
| AC / DC | AC |
| Safety class | 1 |
| IP | IP44 |
| Glow wire test | 650° |
| Direct mounting on normally flammable surfaces | Yes |
| CE | Yes |
| ETL | No |
| Fire Rated (BS 476 PT21 compliant) | No |
| Driver included | Driver |
| Induction | No |
| Emergency mode | No |
| Motion sensor | No |
| Directional | No |
| Tilting | No |
| Walk-over | No |
| Drive-over | No |
| Cable included | No |
| Resin potting | No |
| Type of light emission | Double emission |
| Net weight | 0.960 Kg |

| Finishing casing | |
|------------------|-------------------------|
| Material | Aluminium |
| Colour | embossed white RAL 9003 |
| Processing | Coating |

| Finishing diffuser | |
|--------------------|----------------|
| Material | PMMA |
| Colour | white |
| Processing | Silk-screening |

Wall Lights | 220-240 V | topLED 14 W 350 mA | CRI 80
7908

Double emission wall lights for indoor application. The warm white LED light source with a general lighting light distribution is composed of 36 topLED LEDs with CCT of 3000 K and a CRI 80; the source luminous flux is 1449 lm, with a 103.5 lm/W nominal luminous efficacy.

The device body is made of aluminium and features a embossed white ral 9003 finish, processed by means of coating; the diffuser is made of pmma with a silk-screening treatment; the mounting frame is made of iron, with a white finish, processed by means of coating. The ingress protection degree is IP44; the total weight is of 0.960 kg.

The total absorbed power is 14 W.

The device features protection class I and can be wall lights-mounted.

| Illuminotechnical Features | |
|---------------------------------------|----------------|
| Light Output Ratio (LOR) | 65 % |
| Luminous flux (source) | 1449 lm |
| Luminaire luminous flux | 956 lm |
| Consumption | 14 W |
| Luminaire efficacy | 69 lm/W |
| Colour temperature | 3000 K |
| Standard Deviation of Colour Matching | 3 Step MacAdam |
| Colour rendering index | 80 Ra |
| Life / Failure Ratio | |
| L80 B20 C0 80000h | |

