Floor Lamp | 1 x powerLEDs 12 W 500 mA | RGB 15163





Technical data		
Туре	Floor Lamp	
Installation position	Floor	
Installation environment	Outdoor	
Light Source	LED	
Optics	General Lighting	
Power	12 W	
Current intensity	500mA	
CCT / Tone	RGB	
C.C. / C.V.	CC	
Safety class	3	
IP	IP65	
К	IK10	
Glow wire test	650°	
Direct mounting on normally flammable surfaces	Yes	
CE	Yes	
ETL	No	
Fire Rated (BS 476 PT21 compliant)	No	
Driver included	No	
Induction	No	
Emergency mode	No	
Motion sensor	No	
Directional	No	
Tilting	No	
Walk-over	No	
Drive-over	No	
Cable included	No	
Resin potting	No	
Type of light emission	Double emission	
Net weight	4.700 Kg	

Finishing diffuser

PE

neutral

Material Colour

Colour

Electronics



99140 N/O button Multi Channel and Power 3ch. 190~250V AC / 180~275V DC

Ø 550

Oh!_FL65

Floor Lamp | 1 x powerLEDs 12 W 500 mA | RGB 15163

Double emission floor lamp for outdoor application. The RGB LED light source with a general lighting light distribution is composed of 1 powerleds LEDs.

The diffuser is made of pe; the mounting frame is made of pe, with a white finish. The ingress protection degree is IP65; the total weight is of 4.700 kg. The power supply driver is not provided and is to be ordered separately.

The total absorbed power is 12 W.

The device features protection class III and can be floor-mounted with an outer casing, code 14930(for concrete or masonry).

Oh!_FL65

Oh!_FL65 | Floor Lamp | Accessories 15163

	22 0 11	Outer casing - outer casing for installation on ground or on concrete	Code 14930
	30 30 0 13 0 13	Pegs	Code 14931
71111888	0 34	anti-theft - anti-theft ground fixing bracket	Code 14081