
Ceiling Lights | 220-240 V | 3xE27 90209



| Technical data | |
|--|--------------------------|
| Installation position | Wall lights - Ceiling |
| Installation environment | Indoor |
| Lamp cap | 3 x E27 Max 57W |
| Frequency | 50-60 Hz |
| Optics | General Lighting |
| Light emission direction | frontal |
| Safety class | 1 |
| IP | IP20 |
| Glow wire test | 850° |
| Direct mounting on normally flammable surfaces | Yes |
| CE | Yes |
| ETL | No |
| Fire Rated (BS 476 PT21 compliant) | No |
| Induction | No |
| Emergency mode | No |
| Motion sensor | No |
| Directional | No |
| Tilting | No |
| Walk-over | No |
| Drive-over | No |
| Cable included | No |
| Resin potting | No |
| Type of light emission | Double emission |
| Net weight | 7.005 Kg |
| | |

| Finishing casin | | | |
|------------------|----------------|--|--|
| Material | Iron | | |
| Colour | white | | |
| Processing | Coating | | |
| | | | |
| Finishing diffus | r | | |
| Material | Glass | | |
| Colour | white | | |
| Processing | Silk-screening | | |

Double emission ceiling lights for indoor application. Compatibility: LED lamp, compact fluo 30 W, halogen 57 W; lamp cap 3xE27.

The device body is made of iron and features a white finish, processed by means of coating; the diffuser is made of glass with a silk-screening treatment; the mounting frame is made of iron, with a white finish, processed by means of coating. The ingress protection degree is IP20; the total weight is of 7.005 kg.

The device features protection class I and can be wall lights or ceilingmounted.

| Illuminotechnical Features | | |
|----------------------------|---------|--|
| Luminous flux (source) | 2745 lm | |
| Colour temperature | 2500 K | |
| Colour rendering index | 100 Ra | |