




Wall Lights | 220-240 V | 2xE27
327B921



| Technical data | |
|--|------------------|
| Type | Surface |
| Installation position | Wall lights |
| Installation environment | Indoor |
| Lamp cap | 2 x E27 Max 57W |
| Frequency | 50-60 Hz |
| Optics | General Lighting |
| Light emission direction | frontal |
| Safety class | 1 |
| IP | IP20 |
| Glow wire test | 850° |
| Direct mounting on normally flammable surfaces | Yes |
| CE | Yes |
| ETL | No |
| Fire Rated (BS 476 PT21 compliant) | No |
| Induction | No |
| Emergency mode | No |
| Motion sensor | No |
| Directional | No |
| Tilting | No |
| Walk-over | No |
| Drive-over | No |
| Cable included | No |
| Resin potting | No |
| Type of light emission | Double emission |
| Net weight | 1.130 Kg |

| Finishing diffuser | |
|--------------------|--------------|
| Material | Glass |
| Colour | amber |
| Processing | Sandblasting |



Wall Lights | 220-240 V | 2xE27
327B921

Double emission wall lights for indoor application. Compatibility: LED lamp, halogen 57 W, compact fluo 20 W; lamp cap 2xE27.

The diffuser is made of glass with a sandblasting treatment; the mounting frame is made of iron, with a white finish, processed by means of coating. The ingress protection degree is IP20; the total weight is of 1.130 kg.

The device features protection class I and can be wall lights-mounted.

| Illuminotechnical Features | |
|-----------------------------------|---------|
| Luminous flux (source) | 1830 lm |
| Colour temperature | 2500 K |
| Colour rendering index | 100 Ra |