





Pendant Luminaires | arrayLED 8 W 350 mA | CRI 80  
15111



Technical data	
Type	Surface
Installation position	Ceiling
Installation environment	Outdoor
Light Source	LED
Optics	General Lighting
Light emission direction	downward
Power	8 W
Luminous flux (source)	994 lm
Current intensity	350mA
Frequency	50-60 Hz
CCT / Tone	3000 K
Colour rendering index	80 Ra
C.C. / C.V.	CC
Safety class	3
IP	IP65
Glow wire test	650°
Direct mounting on normally flammable surfaces	Yes
CE	Yes
ETL	No
Fire Rated (BS 476 PT21 compliant)	No
Driver included	No
Induction	No
Emergency mode	No
Motion sensor	No
Directional	No
Tilting	No
Walk-over	No
Drive-over	No
Cable included	No
Resin potting	No
Type of light emission	Single emission

Finishing diffuser	
Material	PE
Colour	neutral



Pendant Luminaires | arrayLED 8 W 350 mA | CRI 80  
15111

Single emission pendant luminaires for outdoor application. The warm white LED light source with a general lighting light distribution is composed of 1 topped LEDs with CCT of 3000 K and a CRI 80; the source luminous flux is 994 lm, with a 124.3 lm/W nominal luminous efficacy.

The diffuser is made of pe; the mounting frame is made of iron, with a embossed white ral 9003 finish, processed by means of coating. The ingress protection degree is IP65; The power supply driver is not provided and is to be ordered separately.


The total absorbed power is 8 W.

The device features protection class III and can be ceiling-mounted.

Illuminotechnical Features	
Light Output Ratio (LOR)	83 %
Luminous flux (source)	994 lm
Luminaire luminous flux	831 lm
Consumption	8 W
Luminaire efficacy	103 lm/W
Colour temperature	3000 K
Standard Deviation of Colour Matching	3 Step MacAdam
Colour rendering index	80 Ra
Life / Failure Ratio	
L80 B20 C0 80h	
UGR	
X=4H   Y=8H	S=0.25H
Reflection factor	70/50/20
UGR transversal	< 25
UGR axial	< 22
OPTICAL	
Light distribution simmetry	Symmetrical
C0/C180 optics	180°



Oh!\_P65 | Pendant Luminaires | Accessories  
15111



Power supply

**Code**

KIT0066