

5STARS 1000 S/I




Part number	04003594
Lampholder:	E40
Wattage:	1x600/1000 W
Finish:	GR-94 / Metallic grey / Textured
Insulation class:	I
Degree of protection:	IP 66
IK-J-xxIP:	IK08 5J xx5
Optic:	SYMMETRIC NARROW REFLECTOR
Ta MIN luminaire:	-20°
Ta MAX luminaire:	45°




Description

- Discharge lamp floodlight for indoor and outdoor lighting, comprising:
- Polyester powder coated die-cast aluminium housing
 - Flat tempered glass diffuser
 - Polished aluminium symmetrical reflector
 - Gaskets made of silicone foam directly applied on glass without joints
 - Electrical wiring box with ignitor, supplied with the luminaire, made of technopolymer reinforced with glass fibre
 - Stainless steel external screws
 - Fully integrated stainless steel aluminium spring clips
 - Powder coated steel bracket
 - Lamp holder box constructed of technopolymer
 - Graduated goniometer for aiming purposes
 - Patented anti-vacuum device
 - Adequate power supply units, available as accessories, must be used for all floodlights

PHOTOMETRIC DATA



TECHNICAL DRAWINGS



5STARS 1000 HQI-T NAV-T



14013320
Aluminium power supply unit IP65, 230 V - 50 Hz, class I, for 1000W high pressure sodium and metal halide lamps with fuse and without ignitor



14215003
Power supply unit with aluminium base and polyamide cover IP65, 230 V - 50 Hz, class I, for 1000 W high pressure sodium and metal halide lamps with fuse and without ignitor



14020701
Power supply unit 230 V - 50Hz, class I, on galvanised steel plate for high pressure sodium and metal halide lamps with fuse and without ignitor

5STARS 600 NAV-T



14017494
Aluminium power supply unit IP65, 230 V - 50 Hz, class I, for 600 W high pressure sodium lamps without ignitor



14017594
Power supply unit with aluminium base and polyamide cover IP65, 230 V - 50 Hz, class I, for 600 W high pressure sodium lamps without ignitor

5STARS 1000 A



14070620
Steel wire lamp steady support (recommended for use in installations subject to heavy vibration) (5STARS 2/A).

5STARS 1000 S



14070520
Steel wire lamp steady support (recommended for use in installations subject to heavy vibration) (5STARS 2/S).

5STARS 1000




14026520
5STARS 2 frosted glass, optional replacement for standard clear glass.



14012320
External anti-glare louvre painted aluminium grey.



14012420
External cowl painted aluminium
grey.



14012520
Steel galvanised wire guard (18
Joule).



14012620
Single 5STARS 2 pole top fitting and
outreach arm for Ø60-76mm poles.



14012720
Twin 5STARS 2 pole top fitting and
outreach arm for Ø60-76mm poles.



14011594
1000mm extension arm in heavy
gauge steel painted aluminium grey.



14044620
5STARS 2 strengthening bracket.
Designed for single point fixing M12-
M14 screw in centre of the bracket.