

## GUELL 1 A/W




<b>Part number</b>	06106994
<b>Lampholder:</b>	LED
<b>Light Source:</b>	LED
<b>Wattage:</b>	39 W
<b>Finish:</b>	GR-94 / Metallic grey / Textured
<b>Insulation class:</b>	I
<b>Degree of protection:</b>	IP 66
<b>IK-J-xxIP:</b>	IK07 3J xx5
<b>CRI:</b>	80
<b>Kelvin:</b>	4000
<b>Power factor:</b>	COSφ ≥ 0,9
<b>Optic:</b>	Asymmetric Wide Reflector
<b>Lightsource lumen output:</b>	5558 lm
<b>Luminaire lumen output:</b>	4712 lm
<b>L:</b>	L70
<b>B:</b>	B10
<b>Lifetime:</b>	150000 h
<b>Ta MIN luminaire:</b>	-20°
<b>Ta MAX luminaire:</b>	40°




### Description

- LED floodlight for indoor and outdoor lighting, comprising:
- Die-cast aluminium housing chemically pre-treated and painted with polyester powder coating
  - Flat tempered glass diffuser
  - Very high performance asymmetrical reflector made of 99.99% plated aluminium, polished, oxidised and free of iridescence
  - Anti-ageing silicone gasket
  - Cable gland M20x1.5 for cables Ø 10- Ø 14 mm
  - Stainless steel external screws
  - Fully integrated stainless steel aluminium spring clips
  - Powder coated steel bracket
  - On request, versions with dimmable ballast available
  - 3000 K and 5000 K available upon request


### PHOTOMETRIC DATA



### TECHNICAL DRAWINGS



## GUELL 1



14172902  
Protective grid GUELL 1




14174220  
Connection box IP 66



14173394  
Wall support 500 mm/19.69" GUELL  
1/2



14173494  
Wall support 1000 mm/39.37" GUELL  
1/2



14453194  
Single pole top support GUELL 1




14453294  
Double pole top support GUELL 1

## GUELL 1 A/W - GUELL 1 S/W



14173294  
Soft glass GUELL 1

## GUELL 1 A/W



14173120  
Louvre GUELL 1 Asymmetrical