


5STARS 2 A/M



Part number	05190094
Lampholder:	Fc2
Light Source:	METAL HALIDE LAMPS
Wattage:	1x250 W
Finish:	GR-94 / Metallic grey / Textured
Insulation class:	I
Degree of protection:	IP 66
IK-J-xxIP:	IK08 5J xx5
Power factor:	COS ϕ \geq 0,9
Optic:	ASYMMETRIC MEDIUM REFLECTOR
Ta MIN luminaire:	-25°
Ta MAX luminaire:	25°




Description


Discharge lamp floodlight for indoor and outdoor lighting, comprising:

- Polyester powder coated die-cast aluminium housing
- Flat tempered glass diffuser
- Polished aluminium asymmetrical reflector
- Gaskets made of silicone foam directly applied on glass without joints
- Cable gland M20x1.5 for cables \varnothing 10- \varnothing 14 mm
- Stainless steel external screws
- Fully integrated stainless steel aluminium spring clips
- Powder coated steel bracket
- Shaped steel gear tray also designed as heat sink
- Graduated goniometer for aiming purposes

PHOTOMETRIC DATA



TECHNICAL DRAWINGS



5STARS 2




14026520
5STARS 2 frosted glass, optional replacement for standard clear glass.



14012320
External anti-glare louvre painted aluminium grey.



14012420
External cowl painted aluminium grey.



14012520
Steel galvanised wire guard (18 Joule).



14044620
5STARS 2 strengthening bracket. Designed for single point fixing M12-M14 screw in centre of the bracket.



14012620
Single 5STARS 2 pole top fitting and outreach arm for Ø60-76mm poles.



14012720
Twin 5STARS 2 pole top fitting and outreach arm for Ø60-76mm poles.



14011594
1000mm extension arm in heavy gauge steel painted aluminium grey.