

## 5STARS 2 A/M



<b>Part number</b>	05190194
<b>Lampholder:</b>	Fc2
<b>Wattage:</b>	1x400 W
<b>Finish:</b>	GR-94 / Metallic grey / Textured
<b>Insulation class:</b>	I
<b>Degree of protection:</b>	IP 66
<b>IK-J-xxIP:</b>	IK08 5J xx5
<b>Power factor:</b>	COS $\phi$ $\geq$ 0,9
<b>Optic:</b>	ASYMMETRIC MEDIUM REFLECTOR
<b>Ta MIN luminaire:</b>	-25°
<b>Ta MAX luminaire:</b>	25°




### Description


Discharge lamp floodlight for indoor and outdoor lighting, comprising:

- Polyester powder coated die-cast aluminium housing
- Flat tempered glass diffuser
- Polished aluminium asymmetrical reflector
- Gaskets made of silicone foam directly applied on glass without joints
- Cable gland M20x1.5 for cables  $\varnothing$  10-  $\varnothing$  14 mm
- Stainless steel external screws
- Fully integrated stainless steel aluminium spring clips
- Powder coated steel bracket
- Shaped steel gear tray also designed as heat sink
- Graduated goniometer for aiming purposes

### PHOTOMETRIC DATA



### TECHNICAL DRAWINGS



## 5STARS 2




14026520  
5STARS 2 frosted glass, optional replacement for standard clear glass.



14012320  
External anti-glare louvre painted aluminium grey.



14012420  
External cowl painted aluminium grey.



14012520  
Steel galvanised wire guard (18 Joule).



14044620  
5STARS 2 strengthening bracket. Designed for single point fixing M12-M14 screw in centre of the bracket.



14012620  
Single 5STARS 2 pole top fitting and outreach arm for Ø60-76mm poles.



14012720  
Twin 5STARS 2 pole top fitting and outreach arm for Ø60-76mm poles.



14011594  
1000mm extension arm in heavy gauge steel painted aluminium grey.